This section describes how to troubleshoot IPv4 and IPv6 access lists (IP-ACLs) created and maintained in the Cisco MDS 9000 Family. It includes the following sections:

Contents

- 1 Overview
 - ♦ 1.1 Protocol Information
 - ♦ 1.2 Address Information
 - ♦ 1.3 Port Information
 - ♦ <u>1.4 ICMP Information</u>
 - ♦ 1.5 ToS Information
- 2 Initial Troubleshooting Checklist
 - ◆ 2.1 Common Troubleshooting Tools in Fabric Manager
 - ◆ 2.2 Common Troubleshooting Commands in the CLI
- 3 IP-ACL Issues
 - ♦ 3.1 All Packets Are Blocked
 - ◆ 3.2 Recreating IP-ACLs Using Fabric Manager
 - ♦ 3.3 Recreating IP-ACLs Using the CLI
 - ♦ 3.4 No Packets Are Blocked
 - ♦ 3.5 PortChannel Not Working with ACL
 - ♦ 3.6 Cannot Remotely Connect to Switch

Overview

IP-ACLs provide basic network security to all switches in the Cisco MDS 9000 Family. IP-ACLs restrict IP-related traffic based on the configured IP filters. A filter contains the rules to match an IP packet, and if the packet matches, the rule also stipulates whether the packet should be permitted or denied.

Each switch in the Cisco MDS 9000 Family can have a maximum of 64 IP-ACLs and each IP-ACL can have a maximum of 256 filters.

An IP filter contains rules for matching an IP packet based on the protocol, address, and port. IPv4 filters can also match on an ICMP type and type of service (ToS).

This section includes the following topics:

- Protocol Information
- Address Information
- Port Information
- ICMP Information
- ToS Information

Contents 1

Protocol Information

You can specify the IP protocol in one of two ways:

- Specify an integer ranging from 0 to 255. This number represents the IP protocol.
- Specify the name of a protocol, restricted to Internet Protocol (IP), Transmission Control Protocol (TCP), User Datagram Protocol (UDP), and Internet Control Message Protocol (ICMP).

Address Information

For IPv4, specify the source and source-wildcard or the destination and destination-wildcard in one of two ways:

- Use the 32-bit quantity in four-part, dotted decimal format (10.1.1.2 0.0.0.0 is the same as host 10.1.1.2).
 - ♦ Each wildcard bit set to zero indicates that the corresponding bit position in the packet's IPv4 address must exactly match the bit value in the corresponding bit position in the source.
 - ♦ Each wildcard bit set to one indicates that both a zero bit and a one bit in the corresponding position of the packet's IPv4 address will be considered a match to this access list entry. Place ones in the binary bit positions you want to ignore and then convert to decimal. For example, use 0.0.255.255 to require an exact match of only the first 16 bits of the source. Wildcard bits set to one must be contiguous and at the end of the prefix. For example, a wildcard of 0.255.0.64 would not be valid.
- Use the **any** option as an abbreviation for a source and source-wildcard or destination and destination-wildcard (0.0.0.0 255.255.255.255)

For IPv6, specify the source or the destination IPv6 addresses in one of two ways:

- Use the 128-bit quantity in colon-separated hexadecimal <prefix>/<length> format. For example, use 2001:0DB8:800:200C::/64 to require an exact match of the first 64 bits of the source.
- Use the **any** option as an abbreviation for a source or destination.

Port Information

To compare the source and destination ports, use the **eq** (equal) option, the **gt** (greater than) option, the **lt** (less than) option, or the **range** (range of ports) option. Table 21-1 displays the port numbers recognized by the Cisco SAN-OS software for associated TCP and UDP ports for IPv4.




Table 21-1 TCP and UDP Port Numbers for IPv4

Port	Number
dns	53
tftp	69
ntp	123
radius accounting	1646 or 1813
radius authentication	1645 or 1812
snmp	161
	dns tftp ntp radius accounting radius authentication

Protocol Information 2

Cisco_MDS_SanOS_Troubleshooting_Guide_--_Troubleshooting_IP_Access_Lists

	snmp-trap	162
	syslog	514
TCP	ftp	20
	ftp-data	21
	ssh	22
	telnet	23
	smtp	25
	tasacs-ds	65
	www	80
	sftp	115
	http	143
	wbem-http	5988
	wbem-https	5989

¹ If the TCP connection is already established, use the **established** option to find matches. A match occurs if the SYN flag is not set in the TCP datagram.

ICMP Information

IP packets can be filtered based on the following optional ICMP conditions:

- The icmp-type: The ICMP message type is a number from 0 to 255.
- The icmp-code: The ICMP message code is a number from 0 to 255.

Table 21-2 displays the value for each ICMP type.

Table 21-2 ICMP Type Value

ICMP Type	Code
echo	8
echo-reply	0
unreachable	3
redirect	5
time exceeded	11
traceroute	30

ToS Information

IPv4 packets can be filtered based on the ToS conditions delay, monetary-cost, normal-service, reliability, and throughput.

Port Information 3

Initial Troubleshooting Checklist

Begin troubleshooting IP-ACLs by checking the following issues:

ChecklistÂ	Check off
Verify licensing requirements. See Cisco MDS 9000 Family Fabric Manager Configuration Guide.	
Verify that the access list has been applied to the interface.	
Verify that the access list is not empty.	
Verify the order of the rules in the access list.	

Common Troubleshooting Tools in Fabric Manager

Choose **Switches > Security > IP ACL** to access IP-ACL configuration.

Common Troubleshooting Commands in the CLI

The following commands may be useful in troubleshooting IP-ACL issues:

- show ip access-list
- show ipv6 access-list
- show interface
- Use the log-deny option at the end of a filter condition to log information about packets that match dropped entries. The log output displays the ACL number, permit or deny status, and port information. Use the following CLI commands to ensure that the debug messages are logged to the logfile for the kernel and ipacl facilities:
- logging logfile SyslogFile 7
- logging level kernel 7
- logging level ipacl 7

IP-ACL Issues

This section describes troubleshooting ACLs and includes the following topics:

- All Packets Are Blocked
- No Packets Are Blocked
- PortChannel Not Working with ACL
- Cannot Remotely Connect to Switch

All Packets Are Blocked

Symptom All packets are blocked.

Table 21-3 All Packets Are Blocked

Symptom Possible Cause	Solution
------------------------	----------

All packets are blocked.	Access list is empty.	Remove the access list from the interface. Choose Switches > Security > IP ACL in Fabric Manager, click the Interfaces tab, and remove the ACL name from the ProfileName field. Click Apply Changes . Use the no ip access-group or the no ipv6 traffic-filter CLI command in interface mode.
	A deny filter is too broad.	Delete the deny filter. Choose Security > IP ACL in Device Manager, right-click the access list, and click Rules. Right-click the filter you want to delete and click Delete. Use the no ip access-list for IPv4-ACLs or no ipv6 access-list for IPv6, and use the no deny CLI command in IP-ACL configuration submode.
	Deny filter is too high in the access list order.	Delete the access list and recreate. See the "Re-creating IP-ACLs Using Fabric Manager" section or the "Re-creating IP-ACLs Using the CLI" section.
	No existing permit filters match the packets.	Add an appropriate permit filter. Choose Security > IP ACL in Device Manager, right-click the access list, and click Rules. Click Create.
		You also can use the ip access-list for IPv4-ACLs or ipv6 access-list for IPv6, and use the permit CLI command in IP-ACL configuration submode.

Recreating IP-ACLs Using Fabric Manager

To re-create an IP-ACL using Fabric Manager, follow these steps:

- 1. Choose **Switches > Security > IP ACL** and select the **Interfaces** tab.
- 2. Right-click all interfaces that have the IP-ACL that you need to modify and remove the IP-ACL name from the ProfileName field.
- 3. Click **Apply Changes** to save these changes.
- 4 Click the **IP** ACL wizard icon. You see the IP-ACL wizard dialog box.
- 5. Add the IP-ACL name in the name field and click **Add**.
- 6. Set the IP address, subnet mask, and protocol.

All Packets Are Blocked 5

- 7. Select **permit** or **deny** from the Action drop-down menu and click **Next**.
- 8. Check the switches that you want to apply this ACL to and click Finish.

Recreating IP-ACLs Using the CLI

To recreate an IP-ACL using the CLI, follow these steps:

1. Use the **show interface** command to determine which interfaces use the ACL.

```
switch# show interface gigabitethernet 2/1
GigabitEthernet2/1 is up
   Hardware is GigabitEthernet, address is 0005.3001.a706
    Internet address(es):
        4000::1/64
        fe80::205:30ff:fe01:a706/64
    MTU 2300 bytes
    Port mode is IPS
    Speed is 1 Gbps
    Beacon is turned off
   Auto-Negotiation is turned on
   ip access-group TCPAlow in
    5 minutes input rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
    5 minutes output rate 0 bits/sec, 0 bytes/sec, 0 frames/sec
    1916 packets input, 114960 bytes
      0 multicast frames, 0 compressed
      0 input errors, 0 frame, 0 overrun 0 fifo
    O packets output, O bytes, O underruns
      O output errors, O collisions, O fifo
      O carrier errors
```

2. Use the **no ip access-group** or the **no ipv6 traffic-filter** command in interface mode to remove the ACL from the interface. Repeat this step for all interfaces found in Step 1.

```
switch(config)# interface gigabitethernet 2/1
switch(config-if)# '''no''' '''ip access-group TCPAlow '''
```

3. Use the **no ip access-list** or the **no ipv6 access-list** command to delete the access list and all filters associated with it.

```
switch(config)# '''no''' '''ip access-list TCPAlow '''
```

Note: We recommend deleting an ACL and recreating it because you cannot change the order of filters in an ACL.

4. Use the **ip access-list** or the **ipv6 access-list** command to create an access list.

```
switch(config)# '''ip access-list List1 permit ip any any '''
```

Tip: Add the filters in priority order. Add a fall-through filter in the case where no filter matches an incoming packet.

5. Use the **ip access-group** or the **ipv6 traffic-filter** command in interface mode to add the ACL to the interface. Repeat this step for all interfaces found in Step 1.

```
switch(config)# interface gigabitethernet 2/1
switch(config-if)# '''ip access-group List1 '''

switch(config)# interface gigabitethernet 2/2
switch(config-if)# '''ipv6 traffic-filter IPAlow ''''
```

No Packets Are Blocked

Symptom No packets are blocked.

Table 21-4 No Packets Are blocked

Symptom	Possible Cause	Solution
No packets are blocked.	A permit filter is too broad.	Delete the permit filter. Add an appropriate permit filter. Choose Security > IP ACL in Device Manager, right-click the access list and click Rules . Right click the rule and click Delete . You can also use the no ip access-list for IPv4-ACLs or no ipv6 access-list for IPv6, and use the no permit CLI command in IP-ACL configuration submode.
	Permit filter is too high in the access list order.	Delete the access list and recreate. See the "Recreating IP-ACLs Using Fabric Manager" section or the "Re-creating IP-ACLs Using the CLI" section.

PortChannel Not Working with ACL

Symptom PortChannel not working with ACL.

Table 21-5 PortChannel Not Working with ACL

Symptom	Possible Cause	Solution
PortChannel not working with ACL	ACL not applied to all interfaces in the PortChannel.	Add the ACL to all interfaces in the PortChannel. Choose Switches > ISLs > Port Channels to view the Members Admin field to find out which interfaces are part of the PortChannel. Choose Switches > Security > IP ACL on Fabric Manager, click the Interfaces

Cisco_MDS_SanOS_Troubleshooting_Guide_--_Troubleshooting_IP_Access_Lists

tab, and add the ACL name to the ProfileName field. Click Apply Changes .
Use the show port-channel database CLI command to find out which interfaces are part of the PortChannel and then use the ip access-group or the ipv6 traffic-filter CLI command in interface mode to add the ACL to all interfaces in the PortChannel.

Cannot Remotely Connect to Switch

Symptom Cannot remotely connect to switch.

Table 21-6 Cannot Remotely Connect to Switch

Symptom	Possible Cause	Solution
Cannot remotely connect to switch.	Incorrect ACL on mgmt0 interface.	Connect to console port locally and delete the ACL. Use the no ip access-group or the no ipv6 traffic-filter CLI command in interface mode.

Back to Main Page: Cisco MDS SAN-OS Troubleshooting Guide