

**Main page:** [Cisco Unified MeetingPlace, Release 7.0](#)

**Up one page:** [Reference Information](#)

Unit Dimensions	<ul style="list-style-type: none"> <li>• Height: 1U (1.75 inches or 44.45 mm)</li> <li>• Width: 17.25 inches (438.15 mm)</li> <li>• Depth: 10 inches (254 mm)</li> <li>• Weight: 4.45 kg (9.81 lbs)-may vary according to configuration</li> </ul>
LED Indicators	<ul style="list-style-type: none"> <li>• Ethernet: <ul style="list-style-type: none"> <li>◆ Link</li> <li>◆ Connection Speed</li> </ul> </li> <li>• ALARM</li> <li>• REG</li> <li>• ACT</li> <li>• Swap RDY</li> </ul>
Push Buttons	<ul style="list-style-type: none"> <li>• RST</li> </ul>
Communication Interfaces	<ul style="list-style-type: none"> <li>• Audio Blade-Ethernet 10/100/1000 Mbps auto-negotiate speed select</li> <li>• Video Blade-Ethernet 10/100 Mbps auto-negotiate speed select</li> <li>• Asynchronous serial port RS-232 connected via 9-pin D-type connector</li> <li>• RJ-45 serial port (for video processing module)</li> <li>• SVGA port (for video processing module)</li> <li>• USB connector (for video processing module)</li> </ul>
Chipset	<ul style="list-style-type: none"> <li>• Audio Blade-MPC8548 at 1.3GHz</li> <li>• Video Blade-PPC7410 at 500MHz and MPC8260 at 333/200MHz</li> </ul>
Operating System	<ul style="list-style-type: none"> <li>• RTOS, VxWorks 6.3</li> </ul>
Memory	<ul style="list-style-type: none"> <li>• Audio Blade-64 MB flash, 512K L-2 Cache at 533MHz, 1GB DDR2 SDRAM at 533MDR (266MHz)</li> <li>• Video Blade-32MB flash, 2M L-2 cache at 250MHz, 256MB SDRAM</li> </ul>
Failsafe	<ul style="list-style-type: none"> <li>• Watchdog timer built in</li> </ul>
Power Supply	<ul style="list-style-type: none"> <li>• Input 100-240VAC autoswitched</li> <li>• Output + 3.3VDC, + 5VDC, + 12VDC</li> <li>• Maximum power load 150W</li> </ul>