

Main page: [Cisco Unified MeetingPlace, Release 7.0](#)

Up one page: [Reference Information](#)

Unit Dimensions	<ul style="list-style-type: none"> • Height: 1U (1.75 inches or 44.45 mm) • Width: 17.25 inches (438.15 mm) • Depth: 10 inches (254 mm) • Weight: 4.45 kg (9.81 lbs)-may vary according to configuration
LED Indicators	<ul style="list-style-type: none"> • Ethernet: <ul style="list-style-type: none"> ◆ Link ◆ Connection Speed • ALARM • REG • ACT • Swap RDY
Push Buttons	<ul style="list-style-type: none"> • RST
Communication Interfaces	<ul style="list-style-type: none"> • Audio Blade-Ethernet 10/100/1000 Mbps auto-negotiate speed select • Video Blade-Ethernet 10/100 Mbps auto-negotiate speed select • Asynchronous serial port RS-232 connected via 9-pin D-type connector • RJ-45 serial port (for video processing module) • SVGA port (for video processing module) • USB connector (for video processing module)
Chipset	<ul style="list-style-type: none"> • Audio Blade-MPC8548 at 1.3GHz • Video Blade-PPC7410 at 500MHz and MPC8260 at 333/200MHz
Operating System	<ul style="list-style-type: none"> • RTOS, VxWorks 6.3
Memory	<ul style="list-style-type: none"> • Audio Blade-64 MB flash, 512K L-2 Cache at 533MHz, 1GB DDR2 SDRAM at 533MDR (266MHz) • Video Blade-32MB flash, 2M L-2 cache at 250MHz, 256MB SDRAM
Failsafe	<ul style="list-style-type: none"> • Watchdog timer built in
Power Supply	<ul style="list-style-type: none"> • Input 100-240VAC autoswitched • Output + 3.3VDC, + 5VDC, + 12VDC • Maximum power load 150W