Main page: Cisco Unified MeetingPlace, Release 7.0

Up one page: Reference Information

Chassis Dimensions	• Height: 2U (3.5 inches or 88.9 mm) • Width: 17.25 inches (438.15 mm) • Depth: 10 inches (254 mm) • Weight: 8 kg (17.64 lbs) empty, 11 kg (24.25 lbs) full-may vary according to configuration
Element Board Dimensions	• Width: 9.19 inches (233.35 mm) • Depth: 6.3 inches (160 mm)
RTM Board Dimensions	• Width: 9.19 inches (233.35 mm) • Depth: 3.15 inches (80 mm)
System Monitoring LED Indicators	• POWER • ALARM • FAN • TEMP
Board LED Indicators (Front Panel)	• Ethernet: ♦ Link ♦ Connection Speed • ALARM • REG • ACT • Swap RDY
Board LED Indicators (Rear panel for Cisco Unified MeetingPlace 3545 Media Server PRI Gateway)	• PRI 1 or 2: ♦ ACT ♦ D-Ch ♦ ALRM
Board LED Indicators (Rear panel for Cisco Unified MeetingPlace 3545 Media Server Serial Gateway)	• PORT 1 to 4: ♦ ACT ♦ ALARM
Push Buttons	• RST (front panel)
Communication Interfaces on Front Panel	• Audio Blade-Ethernet 10/100/1000 Mbps auto-negotiate speed select • Video Blade-Ethernet 10/100 Mbps auto-negotiate speed select

	• Asynchronous serial port RS-232 connected via 9-pin D-type connector
Chipset	• Audio Blade-MPC8548 at 1.3GHz • Video Blade-PPC7410 at 500MHz and MPC8260 at 333/200MHz
Operating System	• RTOS, VxWorks 6.3
Memory	• Audio Blade-64 MB flash, 512K L-2 Cache at 533MHz, 1GB DDR2 SDRAM at 533MDR (266MHz) • Video Blade-32MB flash, 2M L-2 cache at 250MHz, 256MB SDRAM
Failsafe	• Watchdog timer built in
Power supply	• Dual power supply units • Full redundancy • Power on/alarm LED on each unit • Input 100-240VAC, 50/60Hz, autoswitched • Output + 3.3VDC, + 5VDC, ± 12VDC • Maximum power load 300W
Ventilation Fans	• 2 fan units • Brushless 12V DC motor • Locked rotor detection • Polarity protection • Auto-restart capability