

**Main page:** [Cisco Unified MeetingPlace, Release 7.0](#)

**Up one level:** [Configuration](#)

You can define custom fields for meetings, user profiles, and user groups. Use these flex fields to track site- or organization-specific information by meeting or user.

You can set the [Protection level](#) to control which flex fields appear in or can be modified from the end-user web interface.

## Contents

- [1 Table: Default Flex Field Values](#)
- [2 Restrictions](#)
- [3 Procedure](#)
- [4 Related Topics](#)

**Table: Default Flex Field Values**

<b>Type of Flex Field</b>	<b>Default Value of Flex Field</b>
Text	(blank)
Number	0
Date	Jan 01 1970
Yes/No	No

### Restrictions

- Flex fields are not included in exported output.
- Flex fields cannot be imported.
- If you modify the [Type](#) of an existing flex field, the flex field value in existing user groups, user profiles, and meeting records that contain that flex field will be replaced by the *default* value applicable to the newly specified [Type](#). See [Table: Default Flex Field Values](#).

### Procedure

1. Log in to the Administration Center.
2. Click **System Configuration > Flex Fields Configuration**.
3. Click one of the flex field entries.

4. Configure the fields on the [Edit Flex Fields Page](#).
5. Click **Save**.

#### **Related Topics**

- [Table: Field Reference: Edit Flex Fields Page](#)
- [Configuring the Cisco Unified MeetingPlace Web Conferencing User Interface](#)
- [Customizing the Cisco Unified MeetingPlace Scheduling Form for Microsoft Outlook](#)