

Main page: [Cisco Unified MeetingPlace, Release 7.0](#)

Up one level: [Reference Information](#)

Table: Table 5 Export Data Specifications-Outgoing Calls Information

Field Name	Description	Size and Type of Value
StartTimeOfCall	Date and time when the system placed the call.	MM/DD/YYYY HH:MM
uid	<u>User ID</u> of the person who initiated the dial-out call.	1 to 30 alphanumeric characters
ConfNum	See <u>ConfNum</u> .	1 to 9 numeric characters
nSeconds	Duration of the outgoing call, in seconds.	An unsigned integer
CalledDest	Telephone number that was dialed.	No more than 32 ASCII digits
fBlastOutdial	Whether this was a blast dial-out call.	Yes/No
UpdateTime	When this record was most recently updated.	MM/DD/YY HH:MM
PartID	<p>Unique number that identifies each meeting participant. The meeting owner is assigned the number 0. The first non-owner participant is assigned the number 1. As each participant joins, the next incremental number is assigned.</p> <p>If a profiled user leaves and rejoins a meeting, the same PartID is used. If a guest user leaves and rejoins a meeting, a new PartID is used.</p> <p>A PartID of -851969 indicates that the user did not actually join the meeting.</p>	0 to 17 ASCII text characters

Related Topics

- [Running Reports and Exporting Data from Cisco Unified MeetingPlace](#)