Main page: Cisco Unified MeetingPlace Express, Release 2.x

Previous page: Page References

This page is used to configure automatic system backups and archiving.

Table: Fields on the Configure Backup Page

Field	Description	Values
Enable automatic backup	Defines whether to enable the system to automatically perform Level 0 (L0), Level 1(L1), and Level 2 (L2) database backups.	Yes/No Default: Yes
Enable automatic archiving	Defines whether to enable the system to automatically archive the database after a backup.	Yes/No Default: No
Archiving method	Selects the method for archiving the backup files and other critical files. See the How to Back Up, Archive, and Restore Data.	Remote (SSH/rsync) Remote (FTP) Default: Remote (SSH/rsync)
Pathname location of archive	Defines the location of the directory where the archived database is saved.	Any valid directory Default: /dev/null
Remote archive host	Defines the name of the host to which the files are archived.	Host name or IP address of the remote machine Default: localhost
Remote host username	Defines the username used to authenticate to the remote host. **Note:** The remote host username and the remote host password must only contain alpha-numeric characters.	Username used on the remote machine Default: root
Remote host password	Defines the password used to authenticate to the remote host. To ensure security, the password is displayed as asterisks. **Note:** The remote host username and the remote host password must only contain alpha-numeric characters.	Password associated with the username used on the remote machine Default: **********

Notification e-mail	Defines the e-mail address to which the Cisco Unified MeetingPlace Express system sends the archive execution status.	Any valid e-mail address

Related Topics

- Configuring Backups