

Do the following procedure.

**To Enable Cisco Unified MeetingPlace DCTS Addin**

1. Choose Windows **Start** menu > **Programs** > **Cisco MeetingPlace Applications** > **MeetingPlace DCTS Addin** .
2. When the addin application opens, select **Enable MeetingPlace DCTS Addin** .
3. Enter values in fields:

Field	Value
Invoke Server URL	Replace <server> with the hostname of your Envoke Server.
Login UserID	Enter the DCTS login ID.  This ID is specific to the DCTS application and is different from an end-user ID.
Login Password	Enter the DCTS login password.
Cisco Unified MeetingPlace Web URL	Enter the URL of your Cisco Unified MeetingPlace web server.
Organization	Enter the name of your department or organization.  This field is provided for information purposes only.
Update Interval	Enter how often (in milliseconds) you want the Cisco Unified MeetingPlace web server to update the Envoke Server.
Heartbeat Interval	Enter the regular amount of time (in milliseconds) that should pass between the Cisco Unified MeetingPlace web server and Envoke Server before the two exchange information, called <i>heartbeats</i> .  If the Envoke Server does not receive a heartbeat when expected, it assumes that the connection is dead and turns off.

4. Click **Submit**.

5. Restart Cisco Unified MeetingPlace Web.