

**Main page:** [Cisco Unified Presence, Release 7.x](#)

## Contents

- [1 Previous Topic](#)
- [2 Number of Cisco Unified Presence Users Supported](#)
  - ◆ [2.1 Important Note](#)
  - ◆ [2.2 Table: 3 Cisco Unified Presence 7.x Capacities](#)
  - ◆ [2.3 Related Topics](#)
- [3 Number of Microsoft Office Communicator Users Supported](#)
  - ◆ [3.1 Table 4: Microsoft Office Communicator Interoperability](#)
  - ◆ [3.2 Related Topics](#)

### Previous Topic

- [Hardware and Software Compatibility Information for Cisco Unified Presence](#)
- [Number of Cisco Unified Presence Users Supported](#)
- [Number of Microsoft Office Communicator Users Supported](#)

## Number of Cisco Unified Presence Users Supported

The table below identifies the number of users that Cisco Unified Presence Release 7.x can sustain depending on your server type and your deployment strategy.

If you are deploying two or more nodes in your Cisco Unified Presence installation, use the multi-node feature in Cisco Unified Presence and ensure that your hardware is compatible with this feature. This is necessary for both a fresh install and upgrade of Cisco Unified Presence.

### Important Note

- See the *Deployment Guide for Cisco Unified Presence* for more information about specific multi-node deployment strategies and hardware support information for a multi-node deployment.

**Table: 3 Cisco Unified Presence 7.x Capacities**

Cisco Unified Communications Mode		
Deployment Model	Platform Model	Number of Users Supported
Single Node	MCS7816	500
Single Node	MCS7825	1000
Single Node	MCS7835	2500

Single Node	MCS7845	5000
Multi-Node Cluster (6 nodes)	MCS7816	3000
Multi-Node Cluster (6 nodes)	MCS7825	6000
Multi-Node Cluster (6 nodes)	MCS7835	15000
Multi-Node Cluster (6 nodes)	MCS7845	30000

#### Related Topics

- [Codes Used in the Tables in This Document](#)
- [Cisco Unified Presence Hardware Compatibility](#)
- [Cisco Unified Presence Software Compatibility](#)
- [Compatibility with Cisco IP Phones](#)
- [Getting More Information](#)

## Number of Microsoft Office Communicator Users Supported

The Cisco Unified Communications Manager server that you use determines how many users are supported when interoperating with Microsoft Office Communicator. The Cisco Unified Presence server is required only as the gateway and does not limit user capacity. [Table 4: Microsoft Office Communicator Interoperability](#) identifies the number of Microsoft Office Communicator users that are supported per server and per cluster.

**Table 4: Microsoft Office Communicator Interoperability**

Microsoft Office Communicator Interoperability Mode (Microsoft Client Mode)			
Cisco Unified Communication Manager Platform	Number of Microsoft Office Communicator User Supported Per Server	Number of Microsoft Office Communicator User Support Per Cluster	Cisco Unified Presence Server Dependency
MCS7825	900	3600	Cisco Unified Presence serves as the CSTA Gateway.
MCS7835	2000	8000	Cisco Unified Presence serves as the CSTA Gateway.
MCS7845	5000	20000	Cisco Unified Presence serves as the CSTA Gateway.

#### Related Topics

- [Legend: Information Collated in the Compatibility Tables](#)
- [Cisco Unified Presence Hardware Compatibility](#)
- [Cisco Unified Presence Software Compatibility](#)

- [Compatibility with Cisco IP Phones and Third-Party IP Phones](#)
- [Getting More Information](#)