

Cisco_Unity_Connection_APis

Cisco Unity Connection is a feature-rich voice messaging platform based on the same Linux operating system as Cisco Unified Communications Manager. Connection users can access voice messages by using email, web clients, mobile devices, instant messaging, and desktop clients such as Cisco Unified Personal Communicator; and can view, search, sort, and play messages on a Cisco Unified IP Phone display. Connection also provides comprehensive automated-attendant functions, including intelligent call routing and easily customizable call screen and message notification options. For more information see [Cisco Unity Connection documentation on Cisco.com](#).

Cisco Unity Connection includes several Representational State Transfer (REST) application programming interfaces (APIs) that provide provisioning, messaging, and telephony access to Connection. These APIs provide the ability to integrate Connection features into existing enterprise-wide provisioning management systems and messaging clients. The APIs are REST interfaces that standardize operations such as add, delete, view, and modify.

Available Connection REST APIs

CUPI: [Cisco Unity Connection Provisioning Interface \(CUPI\) API](#)

The Cisco Unity Connection Provisioning Interface (CUPI) API provides access to the most commonly provisioned data on Cisco Unity Connection systems?users, contacts, distribution lists, and call handlers.

CUPI for End Users: [Cisco Unity Connection Provisioning Interface \(CUPI\) API -- For End Users](#)

The Cisco Unity Connection Provisioning Interface (CUPI) API includes access for individual users when authenticating against user credentials. This allows for custom end-user applications.

CUMI: [Cisco Unity Connection Messaging Interface \(CUMI\) API](#)

The Cisco Unity Connection Messaging Interface (CUMI) API provides access to user messages.

CUTI: [Cisco Unity Connection Telephony Interface \(CUTI\) API](#)

The Cisco Unity Connection Telephony Interface (CUTI) API provides the ability to play and record audio content over the phone.

CUII: [Cisco Unity Connection Imaging Interface \(CUII\) API](#)

Cisco Unity Connection 9.0(1) and later versions now support the Cisco Unity Connection Imaging Interface (CUII) API that provides the ability to view message state and mailbox information visually using graphics icons.

CUNI: Cisco Unity Connection Notification Interface (CUNI) API

The Cisco Unity Connection Notification Interface (CUNI) API provides notification for one or more users. CUNI is designed for use in server-to-server applications where receiving notifications for many users over a single connection is required.

Other Connection API Resources

FAQ

Troubleshooting

Draft