

Links to Other API pages: [Cisco Unity Connection APIs](#)

| |
|---|
| CUPI Guide Contents |
| API Overview |
| Index of All CUPI Documentation |

Contents

- [1 Reading a User's Information](#)
- [2 Creating a User](#)
- [3 Modifying a User](#)
- [4 Deleting a User](#)
- [5 Searching for a User](#)
- [6 Reset the MWI for a User](#)

Reading a User's Information

To read a user's information, do the following GET request:

```
GET http://<connection-server>/vmrest/users/{objectid}
```

Creating a User

To create a user account, do the following POST request:

```
POST http://<connection-server>/vmrest/users?templateAlias=voicemailusertemplate
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<User>
<Alias>jdoe</Alias>
<DtmfAccessId>7890</DtmfAccessId>
</User>
```

The following is the result of the above POST request:

```
201 Created
```

The HTTP response will include the full URI to the newly created user in the Location header.

Modifying a User

To modify a user account, do the following PUT request:

```
PUT http://<connection-server>/vmrest/users/{objectid}
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<User>
```

```
<DisplayName>johnd</DisplayName>  
</User>
```

The following is the result of the above PUT request:

```
204 Accepted
```

Deleting a User

To delete a user account, do the following DELETE request:

```
DELETE http://<connection-server>/vmrest/users/{objectid}
```

The following is the result of the above DELETE request:

```
200 OK
```

Searching for a User

To search for a user account, do the following GET request:

```
GET http://<connection-server>/vmrest/users?query=(alias%20startswith%20ab)
```

Reset the MWI for a User

The reset the MWI for a user :

```
POST http://<connection-server>/vmrest/users/{objectid}?method=resetmwi
```