

Links to Other API pages: [Cisco Unity Connection APIs](#)

CUPI Guide Contents
<u>API Overview</u>
<u>Index of All CUPI Documentation</u>

Contents

- [1 Message Settings APIs](#)
 - ◆ [1.1 Updating a Message Setting](#)

Message Settings APIs

Administrator can use this API to fetch the message settings.

Updating a Message Setting

The following is an example of the PUT request that updates the message settings:

```
PUT https://<connection-server>/vmrest/callhandlertemplates/<callhandler-objectid>
Request Body:
<CallhandlerTemplate>
  <AfterMessageAction>2</AfterMessageAction>
  <AfterMessageTargetConversation>SystemTransfer</AfterMessageTargetConversation>
</CallhandlerTemplate>
```

The following is the response from the above *PUT* request and the actual response will depend upon the information given by you:

Response Code: 204

JSON Example

To update message setting, do the following:

```
Request URI:
PUT: https://<connection-server>/vmrest/callhandlertemplates/<calhandler-objectid>
Accept: application/json
Content_type: application/json
Connection: keep_alive
Request Body:
{
  "AfterMessageAction": "2",
  "AfterMessageTargetConversation": "SystemTransfer"
}
```

The following is the response from the above *PUT* request and the actual response will depend upon the information given by you:

Response Code: 204