

Links to Other API pages: [Cisco Unity Connection APIs](#)

CUPI Guide Contents
API Overview
Index of All CUPI Documentation

Contents

- [1 Private List API](#)
 - ◆ [1.1 Listing All the Private Lists](#)
 - ◆ [1.2 Listing a Particular Private List](#)
 - ◆ [1.3 Create a Private list](#)
 - ◆ [1.4 Update Private List](#)
 - ◆ [1.5 Delete Private List](#)
 - ◆ [1.6 Explanation of Data Fields](#)

Private List API

Listing All the Private Lists

GET https://<connection-server>/vmrest/users/<user-objectid>/privatelists

The following is the response from the above *GET* request and the actual response will depend upon the information given by you:

```
<PrivateLists total="1">
  <PrivateList>
    <URI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c</URI>
    <ObjectId>8465e5d7-f0d2-4d32-81b1-634a2315db9c</ObjectId>
    <DisplayName>Test1</DisplayName>
    <UserObjectId>9375d893-c8eb-437b-90bf-7de4b1d0c3e8</UserObjectId>
    <UserURI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8</UserURI>
    <DtmfName>83781</DtmfName>
    <Alias>Texoma_8465e5d7-f0d2-4d32-81b1-634a2315db9c</Alias>
    <NumericId>1</NumericId>
    <IsAddressable>true</IsAddressable>
    <PrivateListMembersURI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c/privateListMembersURI
    <AlternateNamesURI>/vmrest/alternatenames?query=(PersonalGroupObjectId%20is%208465e5d7-f0d2-4d32-81b1-634a2315db9c)
  </PrivateList>
</PrivateLists>
```

Response Code: 200

Listing a Particular Private List

GET https://<connection-server>/vmrest/users/<user-objectid>/privatelists/<objectid>

The following is the response from the above *GET* request and the actual response will depend upon the information given by you:

```
<PrivateList>
  <URI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c/</URI>
  <ObjectId>8465e5d7-f0d2-4d32-81b1-634a2315db9c</ObjectId>
  <DisplayName>Test1</DisplayName>
  <UserObjectId>9375d893-c8eb-437b-90bf-7de4b1d0c3e8</UserObjectId>
  <UserURI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8</UserURI>
  <DtmfName>83781</DtmfName>
  <Alias>Texoma_8465e5d7-f0d2-4d32-81b1-634a2315db9c</Alias>
  <NumericId>1</NumericId>
  <IsAddressable>true</IsAddressable>
  <PrivateListMembersURI>/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c/members/</PrivateListMembersURI>
  <AlternateNamesURI>/vmrest/alternatenames?query=(PersonalGroupObjectId%20is%208465e5d7-f0d2-4d32-81b1-634a2315db9c)</AlternateNamesURI>
</PrivateList>
```

Response Code: 200

JSON Example

GET https://<connection-server>/vmrest/users/<user-objectid>/privatelists/<objectid>
Accept: application/json
Connection: keep-alive

The following is the response from the above *GET* request and the actual response will depend upon the information given by you:

```
{
  ?URI?: ?/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c/
  ?ObjectId?: ?8465e5d7-f0d2-4d32-81b1-634a2315db9c?
  ?DisplayName?: ?Test1?
  ?UserObjectId?: ?9375d893-c8eb-437b-90bf-7de4b1d0c3e8?
  ?UserURI?: ?/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8?
  ?DtmfName?: ?83781?
  ?Alias?: ?Texoma_8465e5d7-f0d2-4d32-81b1-634a2315db9c?
  ?NumericId?: ?1?
  ?IsAddressable?: ?true?
  ?PrivateListMembersURI?: ?/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/8465e5d7-f0d2-4d32-81b1-634a2315db9c/members/?
  ?AlternateNamesURI?: ?/vmrest/alternatenames?query=(PersonalGroupObjectId%20is%208465e5d7-f0d2-4d32-81b1-634a2315db9c)?
}
```

Response Code: 200

Create a Private list

The mandatory field for creation is DisplayName.

POST https://<connection-server>/vmrest/users/<user-objectid>/privatelists

```
<PrivateList>
  <DisplayName>Test1</DisplayName>
</PrivateList>
```

Cisco_Unity_Connection_Provisioning_Interface_(CUPI)_API_--_User_Private_List_API

The following is the response from the above *POST* request and the actual response will depend upon the information given by you:

Response Code: 201

/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/2375d893-c8eb-437b-90bf-7de4b1d0c3

JSON Example

```
POST https://<connection-server>vmrest/users/<user-objectid>/privatelists/<objectid>
Accept: application/json
Content-type: application/json
Connection: keep-alive
```

```
{
  "DisplayName": "Test1"
}
```

The following is the response from the above *POST* request and the actual response will depend upon the information given by you:

Response code: 201

/vmrest/users/9375d893-c8eb-437b-90bf-7de4b1d0c3e8/privatelists/2375d893-c8eb-437b-90bf-7de4b1d0c3

Update Private List

```
PUT https://<connection-server>vmrest/users/<user-objectid>/privatelists/<objectid>
```

```
<PrivateList>
  <DisplayName>Test11</DisplayName>
</PrivateList>
```

The following is the response from the above *PUT* request and the actual response will depend upon the information given by you:

Response Code: 204

JSON Example

```
PUT https://<connection-server>vmrest/users/<user-objectid>/privatelists/<objectid>
Accept: application/json
Content-type: application/json
Connection: keep-alive
```

```
{
  "DisplayName": "Test11"
}
```

The following is the response from the above *PUT* request and the actual response will depend upon the information given by you:

Response Code: 204

Delete Private List

```
DELETE https://<connection-server>/vmrest/users/<user-objectid>/privatelists/<objectid>
```

Cisco_Unity_Connection_Provisioning_Interface_(CUPI)_API_--_User_Private_List_API

The following is the response from the above *DELETE* request and the actual response will depend upon the information given by you:

Response Code: 204

JSON Example

```
DELETE https://<connection-server>vmrest/users/<user-objectid>/privatelists/<objectid>
Accept: application/json
Connection: keep-alive
```

The following is the response from the above *DELETE* request and the actual response will depend upon the information given by you:

Response code: 204

Explanation of Data Fields

Field Name	Data Type	Operation	Description
DisplayName	String	Read/Write	The preferred text name of the list to be used when displaying entries such as in the administrative console, e.g. Cisco Unity Connection Administration.
UserObjectId	String(36)	Read Only	The unique identifier of the User object to which this list belongs.
DtmfName	String	Read Only	The digits corresponding to the numeric keypad mapping on a standard touchtone phone representing the group name. These digits would need to be dialed to address a message to this list via the phone.
Alias	String	Read Only	The unique text name for either a list
NumericId	String	Read Only	If being used as a personal voicemail list (i.e., "private" voicemail list), the numeric identifier for the personal group,(Value 0-4)
IsAddressable	Boolean	Read Only	A flag indicating whether the entity to which the alias belongs is addressable. Possible Values: <ul style="list-style-type: none">• false: The entity is not addressable• true: The entity is addressable. Default value: true
ObjectId	String(36)	Read Only	Unique identifier of private List