

**Links to Other API pages:** [Cisco Unity Connection APIs](#)

<b>CUPI Guide Contents</b>
<a href="#">API Overview</a>
<a href="#">Index of All CUPI Documentation</a>

## Contents

- [1 SMTP Proxy Address API](#)
  - ◆ [1.1 Listing the SMTP proxy Address](#)
  - ◆ [1.2 Create an SMTP Proxy Address](#)
  - ◆ [1.3 Update SMTP proxy Address](#)
  - ◆ [1.4 Delete SMTP Proxy Address](#)
  - ◆ [1.5 Explanation of Data Fields](#)

## SMTP Proxy Address API

### Listing the SMTP proxy Address

GET https://<connection-server>/vmrest/smtpproxyaddresses?query=(GlobalUserObjectId%20is%20<user-c

The following is the response from the above \*GET\* request and the actual response will depend upon the information given by you:

```
<SmtpproxyAddresses total="2">
  <SmtpproxyAddress>
    <URI>/vmrest/smtpproxyaddresses/3d71d2ed-5baf-48c4-bf25-875bca56e30e</URI>
    <ObjectId>3d71d2ed-5baf-48c4-bf25-875bca56e30e</ObjectId>
    <SmtpproxyAddress>chhavi@we.com</SmtpproxyAddress>
    <ObjectGlobalUserObjectId>9375d893-c8eb-437b-90bf-7de4b1d0c3e8</ObjectGlobalUserObjectId>
    <ObjectGlobalUserURI>/vmrest/globalusers/9375d893-c8eb-437b-90bf-7de4b1d0c3e8</ObjectGlobalUserURI>
  </SmtpproxyAddress>
  <SmtpproxyAddress>
    <URI>/vmrest/smtpproxyaddresses/062fc8cc-a0aa-4ad7-b74c-9589dd95cb1c</URI>
    <ObjectId>062fc8cc-a0aa-4ad7-b74c-9589dd95cb1c</ObjectId>
    <SmtpproxyAddress>chhavi@5.co</SmtpproxyAddress>
    <ObjectGlobalUserObjectId>9375d893-c8eb-437b-90bf-7de4b1d0c3e8</ObjectGlobalUserObjectId>
    <ObjectGlobalUserURI>/vmrest/globalusers/9375d893-c8eb-437b-90bf-7de4b1d0c3e8</ObjectGlobalUserURI>
  </SmtpproxyAddress>
</SmtpproxyAddresses>
```

Response Code: 200

### JSON Example

```
GET https://<connection-server>/vmrest/smtpproxyaddresses?query=(GlobalUserObjectId%20is%20<user-c
Accept: application/json
Connection: keep-alive
```

## Cisco\_Unity\_Connection\_Provisioning\_Interface\_(CUPI)\_API\_--\_User\_SMTP\_Proxy\_Address

The following is the response from the above \*GET\* request and the actual response will depend upon the information given by you:

```
{
  "@total": "2",
  "SmtproxyAddress":
  [
    {
      "URI": "/vmrest/smtproxyaddresses/3d71d2ed-5baf-48c4-bf25-875bca56e30e",
      "ObjectId": "3d71d2ed-5baf-48c4-bf25-875bca56e30e",
      "SmtAddress": "john@we.com",
      "ObjectGlobalUserObjectId": "9375d893-c8eb-437b-90bf-7de4b1d0c3e8",
      "ObjectGlobalUserURI": "/vmrest/globalusers/9375d893-c8eb-437b-90bf-7de4b1d0c3e8"
    },
    {
      "URI": "/vmrest/smtproxyaddresses/062fc8cc-a0aa-4ad7-b74c-9589dd95cb1c",
      "ObjectId": "062fc8cc-a0aa-4ad7-b74c-9589dd95cb1c",
      "SmtAddress": "mary@5.co",
      "ObjectGlobalUserObjectId": "9375d893-c8eb-437b-90bf-7de4b1d0c3e8",
      "ObjectGlobalUserURI": "/vmrest/globalusers/9375d893-c8eb-437b-90bf-7de4b1d0c3e8"
    }
  ]
}
```

Response Code: 200

## Create an SMTP Proxy Address

The mandatory fields for creation are SmtAddress and ObjectGlobalUserObjectId

POST https://<connection-server>vmrest/smtproxyaddresses

```
<SmtproxyAddress>
  <SmtAddress>Texoma@cisco.com</SmtAddress>
  <ObjectGlobalUserObjectId>9375d893-c8eb-437b-90bf-7de4b1d0c3e8</ObjectGlobalUserObjectId>
</SmtproxyAddress>
```

The following is the response from the above \*POST\* request and the actual response will depend upon the information given by you:

Response Code: 201

/vmrest/smtproxyaddresses/8375d893-c8eb-437b-90bf-7de4b1d0c3e8

## JSON Example

POST https://<connection-server>vmrest/smtproxyaddresses

```
Accept: application/json
Content-type: application/json
Connection: keep-alive
```

```
{
  "SmtAddress": "Texoma@cisco.com",
  "ObjectGlobalUserObjectId": "9375d893-c8eb-437b-90bf-7de4b1d0c3e8"
}
```

The following is the response from the above \*POST\* request and the actual response will depend upon the information given by you:

Response Code: 201

## Cisco\_Unity\_Connection\_Provisioning\_Interface\_(CUPI)\_API\_--\_User\_SMTP\_Proxy\_Address

/vmrest/smtpproxyaddresses/8375d893-c8eb-437b-90bf-7de4b1d0c3e8

### Update SMTP proxy Address

PUT https://<connection-server>/vmrest/smtpproxyaddresses/<objectid>

```
<SmtpProxyAddress>
  <SmtpAddress>Texoma@cisco.com</SmtpAddress>
</SmtpProxyAddress>
```

The following is the response from the above \*PUT\* request and the actual response will depend upon the information given by you:

Response Code: 204

### JSON Example

```
PUT https://<connection-server>vmrest/smtpproxyaddresses/<object_id>
Accept: application/json
Content-type: application/json
Connection: keep-alive
```

```
{
  "SmtpAddress": "Texoma@cisco.com"
}
```

The following is the response from the above \*PUT\* request and the actual response will depend upon the information given by you:

Response Code: 204

### Delete SMTP Proxy Address

DELETE https://<connection-server>/vmrest/smtpproxyaddresses/<objectid>

The following is the response from the above \*DELETE\* request and the actual response will depend upon the information given by you:

Response Code: 204

### JSON Example

```
DELETE https://<connection-server>vmrest/smtpproxyaddresses/<objectid>
Accept: application/json
Content-type: application/json
Connection: keep-alive
```

The following is the response from the above \*DELETE\* request and the actual response will depend upon the information given by you:

Response Code: 204

### Explanation of Data Fields

Field Name	Data Type	Operation	Description
------------	-----------	-----------	-------------

Cisco\_Unity\_Connection\_Provisioning\_Interface\_(CUPI)\_API\_--\_User\_Smtp\_Proxy\_Address

ObjectId	String(36)	Read Only	The primary key for this table.
SmtpAddress	String(320)	Read/Write	The full SMTP proxy address for this object.
ObjectGlobalUserObjectId	String(36)	Read/Write	The unique identifier of the Global User to which this SMTP address belongs.