

## ICM Calls are failing because IVR sends wrong values to ICM for the call variables

<b>Problem Summary</b>	ICM Calls are failing because IVR sends wrong values to ICM for the call variables. Or it could be any of the following: 1) ECC variables not passed back to IVR 2) After agent xfer back to same IVR script, no CED sent in response
<b>Error Message</b>	ICM calls are failing.
<b>Possible Cause</b>	This is particularly seen in scenarios when IVR transfers a call to an agent and the agent transfers this call to another IVR script. This results in wrong context being set in IVR, due to which it sends stale values for the call variables to ICM. Look for the following RUN_SCRIPT_RESULT message in the MIVR logs, which has the values for call variables:  793548: Mar 03 12:04:37.044 CET %MIVR-LIB_ICM-7-SENDING_MSG:Sending an ICM message: ICM_MESSAGE=[id=1,value=1],callVariable4=,callVariable5=,callVariable6=,callVariable7=,callVariable8=,callVariable9=,callVariable10=,ecc=[id=41,value=454516],ecc=[id=23,value=0],ecc=[id=4,value=454516],ecc=[id=45,value=0],ecc=[id=...
<b>Recommended Action</b>	There are 3 known defects related to this issue, all of these are fixed in 7.0. Apply ES for the defects related to this issue.
<b>Release</b>	7.0 .
<b>Associated CDETS #</b>	CSCte04762, CSCsu72575, CSCsv96997.