

Ladder\_6

**Back to: Call Flow Details for CUBE Inbound Dial Peer Recording**

**Back to: Call Flow Details for Cisco MediaSense**

**Back to: category: Cisco MediaSense**

---

LE1 -> 172.27.185.128  
RE1 -> 10.10.10.20  
RE2 -> 28282828  
CUBE -> 10.194.122.73

-----  
TIME STAMP UCM CUBE CVP ORA  
-----

--> Initial call 1019 to CVP to 1020, recording established

```
11:04:43.266|-----> | | INVITE sip:5200201005@10.194.122.73:5060 SIP/2.0 (CSEQ : 1
11:04:43.270| | ----->| | INVITE sip:5200201005@10.10.10.20:5060 SIP/2.0 (CSEQ : 101
11:04:43.270|<----- | | SIP/2.0 100 Trying (CSEQ : 101 INVITE)
11:04:43.274| | <-----| | SIP/2.0 100 Trying (CSEQ : 101 INVITE)
11:04:43.306| | <-----| | SIP/2.0 180 Ringing (CSEQ : 101 INVITE)
11:04:43.306|<----- | | SIP/2.0 180 Ringing (CSEQ : 101 INVITE)
11:04:45.294| | <-----| | SIP/2.0 183 Session Progress (CSEQ : 101 INVITE) [With Bod
11:04:45.298|<----- | | SIP/2.0 183 Session Progress (CSEQ : 101 INVITE) [With Bod
11:04:45.298| | <-----| | SIP/2.0 200 Ok (CSEQ : 101 INVITE) [With Body]
11:04:45.298|<----- | | SIP/2.0 200 OK (CSEQ : 101 INVITE) [With Body]
11:04:45.362|-----> | | ACK sip:5200201005@10.194.122.73:5060;transport=tcp SIP/2.
11:04:45.366| | ----->| | ACK sip:10.10.10.20:5060;transport=udp SIP/2.0 (CSEQ : 101
11:04:45.366| | ----->| | INVITE sip:28282828@sjea080:5060 SIP/2.0 (CSEQ : 101 INVIT
11:04:45.382| | <----->| | SIP/2.0 180 Ringing (CSEQ : 101 INVITE)
11:04:45.410| | <-----| | INVITE sip:1019@10.10.10.60:5060 SIP/2.0 (CSEQ : 1 INVITE)
11:04:45.410| | ----->| | SIP/2.0 100 Trying (CSEQ : 1 INVITE)
11:04:45.410|<----- | | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:04:45.414|-----> | | SIP/2.0 100 Trying (CSEQ : 101 INVITE)
11:04:45.414|-----> | | SIP/2.0 200 OK (CSEQ : 101 INVITE) [With Body]
11:04:45.418|<----- | | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:04:45.418| | ----->| | SIP/2.0 200 OK (CSEQ : 1 INVITE) [With Body]
11:04:45.430| | <-----| | ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 1 ACK)
11:04:45.598| | <----->| | SIP/2.0 200 Ok (CSEQ : 101 INVITE) [With Body]
11:04:45.602| | ----->| | ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:04:45.602| | ----->| | INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:04:45.638| | <----->| | SIP/2.0 200 Ok (CSEQ : 102 INVITE) [With Body]
11:04:45.638| | ----->| | ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
```

-----  
TIME STAMP UCM CUBE CVP ORA  
-----

--> 1020 initiates a conference with 1021 (1019 hears MOH)

```
11:04:51.103| | <-----| | INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 2 INVITE)
11:04:51.107| | ----->| | SIP/2.0 100 Trying (CSEQ : 2 INVITE)
11:04:51.107|<----- | | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:04:51.111|-----> | | SIP/2.0 100 Trying (CSEQ : 102 INVITE)
11:04:51.111|-----> | | SIP/2.0 200 OK (CSEQ : 102 INVITE) [With Body]
11:04:51.111|<----- | | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:04:51.111| | ----->| | SIP/2.0 200 OK (CSEQ : 2 INVITE) [With Body]
11:04:51.127| | <-----| | ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 2 ACK)
11:04:51.127| | ----->| | INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:04:51.139| | <----->| | SIP/2.0 200 Ok (CSEQ : 103 INVITE) [With Body]
```

## Ladder\_6

```

11:04:51.143|          | ----->| ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:04:51.243|          | <-----| INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 3 INVITE)
11:04:51.243|          | ----->| SIP/2.0 100 Trying (CSEQ : 3 INVITE)
11:04:51.243|<-----|          | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:04:51.243|----->|          | SIP/2.0 100 Trying (CSEQ : 103 INVITE)
11:04:51.263|----->|          | SIP/2.0 200 OK (CSEQ : 103 INVITE) [With Body]
11:04:51.263|          | ----->| SIP/2.0 200 OK (CSEQ : 3 INVITE) [With Body]
11:04:51.279|          | <-----| ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 3 ACK) [With
11:04:51.283|<-----|          | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:04:51.283|          | ----->| INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:04:51.299|          | <-----| SIP/2.0 200 Ok (CSEQ : 104 INVITE) [With Body]
11:04:51.299|          | ----->| ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0

```

```

-----
TIME STAMP  UCM      CUBE      CVP  ORA
-----

```

--> 1021 answers. 1020 and 1021 are connected, 1019 still listening to music.

```

11:05:09.047|          | <-----| INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 4 INVITE)
11:05:09.047|          | ----->| SIP/2.0 100 Trying (CSEQ : 4 INVITE)
11:05:09.047|<-----|          | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:05:09.051|----->|          | SIP/2.0 100 Trying (CSEQ : 104 INVITE)
11:05:09.051|----->|          | SIP/2.0 200 OK (CSEQ : 104 INVITE) [With Body]
11:05:09.055|<-----|          | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:05:09.055|          | ----->| SIP/2.0 200 OK (CSEQ : 4 INVITE) [With Body]
11:05:09.075|          | <-----| ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 4 ACK)
11:05:09.075|          | ----->| INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:05:09.087|          | <-----| SIP/2.0 200 Ok (CSEQ : 105 INVITE) [With Body]
11:05:09.087|          | ----->| ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:05:09.291|          | <-----| INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 5 INVITE)
11:05:09.291|          | ----->| SIP/2.0 100 Trying (CSEQ : 5 INVITE)
11:05:09.291|<-----|          | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:05:09.291|----->|          | SIP/2.0 100 Trying (CSEQ : 105 INVITE)
11:05:09.307|----->|          | SIP/2.0 200 OK (CSEQ : 105 INVITE) [With Body]
11:05:09.311|          | ----->| SIP/2.0 200 OK (CSEQ : 5 INVITE) [With Body]
11:05:09.327|          | <-----| ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 5 ACK) [With
11:05:09.331|<-----|          | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:05:09.331|          | ----->| INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:05:09.343|          | <-----| SIP/2.0 200 Ok (CSEQ : 106 INVITE) [With Body]
11:05:09.343|          | ----->| ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:05:09.507|          | <-----| UPDATE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 6 UPDATE)
11:05:09.507|<-----|          | UPDATE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:05:09.507|          | ----->| SIP/2.0 200 OK (CSEQ : 6 UPDATE)
11:05:09.511|----->|          | SIP/2.0 200 OK (CSEQ : 106 UPDATE)
11:05:09.511|<-----|          | UPDATE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:05:09.515|----->|          | SIP/2.0 200 OK (CSEQ : 107 UPDATE)

```

```

-----
TIME STAMP  UCM      CUBE      CVP  ORA
-----

```

--> 1020 completes the transfer. All three endpoints are connected to conference bridge (participa

```

11:10:26.037|          | <-----| INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 7 INVITE)
11:10:26.041|          | ----->| SIP/2.0 100 Trying (CSEQ : 7 INVITE)
11:10:26.041|<-----|          | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:10:26.045|----->|          | SIP/2.0 100 Trying (CSEQ : 108 INVITE)
11:10:26.045|----->|          | SIP/2.0 200 OK (CSEQ : 108 INVITE) [With Body]
11:10:26.049|<-----|          | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:10:26.049|          | ----->| SIP/2.0 200 OK (CSEQ : 7 INVITE) [With Body]
11:10:26.065|          | <-----| ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 7 ACK)
11:10:26.065|          | ----->| INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:10:26.089|          | <-----| SIP/2.0 200 Ok (CSEQ : 107 INVITE) [With Body]

```

## Ladder\_6

```
11:10:26.089|          | ----->| ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:10:26.253|          | <-----| | UPDATE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 8 UPDATE)
11:10:26.253|<-----|          | | UPDATE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:10:26.253|          | ----->| | SIP/2.0 200 OK (CSEQ : 8 UPDATE)
11:10:26.257|----->|          | | SIP/2.0 200 OK (CSEQ : 109 UPDATE)
11:10:26.257|<-----|          | | UPDATE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:10:26.257|----->|          | | SIP/2.0 200 OK (CSEQ : 110 UPDATE)
11:10:26.269|          | <-----| | INVITE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 9 INVITE)
11:10:26.269|          | ----->| | SIP/2.0 100 Trying (CSEQ : 9 INVITE)
11:10:26.269|<-----|          | | INVITE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0
11:10:26.269|----->|          | | SIP/2.0 100 Trying (CSEQ : 111 INVITE)
11:10:26.289|----->|          | | SIP/2.0 200 OK (CSEQ : 111 INVITE) [With Body]
11:10:26.289|          | ----->| | SIP/2.0 200 OK (CSEQ : 9 INVITE) [With Body]
11:10:26.313|          | <-----| | ACK sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 9 ACK) [With
11:10:26.317|<-----|          | | ACK sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:10:26.317|          | ----->| | INVITE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2
11:10:26.325|          | <-----| | SIP/2.0 200 Ok (CSEQ : 108 INVITE) [With Body]
11:10:26.329|          | ----->| | ACK sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
```

```
-----
TIME STAMP  UCM      CUBE      CVP  ORA
-----
```

--> 1020 disconnects

```
11:10:40.829|          | <-----| | BYE sip:1020@10.10.10.60:5060 SIP/2.0 (CSEQ : 10 BYE)
11:10:40.829|<-----|          | | BYE sip:1019@172.27.185.128:5060;transport=tcp SIP/2.0 (CS
11:10:40.829|          | ----->| | SIP/2.0 200 OK (CSEQ : 10 BYE)
11:10:40.829|          | ----->| | BYE sip:28282828@10.194.122.80:5060;transport=tcp SIP/2.0
11:10:40.833|----->|          | | SIP/2.0 200 OK (CSEQ : 112 BYE)
11:10:40.837|          | <-----| | SIP/2.0 200 Ok (CSEQ : 109 BYE)
```