This chapter explains how to provision a single Cisco ONS 15454 node and turn it up for service, including assigning a node name, date and time, timing references, network attributes such as IP address and default router, users and user security, and card protection groups.

# Contents

- <u>1 Before You Begin</u>
- <u>2 NTP-A323 Verify Card Installation</u>
- <u>3 NTP-A30 Create Users and Assign Security</u>
- 4 NTP-A25 Set Up Name, Date, Time, and Contact Information
- <u>5 NTP-A261 Set Power Monitor Thresholds</u>
- <u>6 NTP-A169 Set Up CTC Network Access</u>
- 7 NTP-A358 Set up the ONS 15454 in Secure Mode
- <u>8 NTP-A360 Enable EMS Secure Access</u>
- 9 NTP-A27 Set Up the ONS 15454 for Firewall Access
  - ♦ <u>9.1 Figure 4-1: Nodes Behind a Firewall</u>
  - 9.2 Figure 4-2: CTC Computer and ONS 15454s Residing
  - Behind Firewalls
- <u>10 NTP-A355 Create FTP Host</u>
- <u>11 NTP-A28 Set Up Timing</u>
- <u>12 NTP-A324 Create Protection Groups</u>
  - ♦ <u>12.1 Table 4-1: Card Protection Types</u>
- <u>13 NTP-A256 Set Up SNMP</u>
  - ◆ <u>13.1 Figure 4-3: Creating an SNMP Trap</u>
- <u>14 NTP-A318 Provision OSI</u>

## **Before You Begin**

Complete the procedures applicable to your site plan from the following chapters:

- Install the Shelf and Backplane Cable
- Install Cards and Fiber-Optic Cable
- Connect the PC and Log into the GUI

This section lists the chapter procedures (NTPs). Turn to a procedure for applicable tasks (DLPs).

- 1. NTP-A323 Verify Card Installation-Complete this procedure first.
- 2. <u>NTP-A30 Create Users and Assign Security</u>-Complete this procedure to create Cisco Transport Controller (CTC) users and assign their security levels.
- 3. <u>NTP-A25 Set Up Name, Date, Time, and Contact Information</u>-Continue with this procedure to set the node name, date, time, location, and contact information.
- 4. <u>NTP-A261 Set Power Monitor Thresholds</u>-Continue with this procedure to set the node battery power thresholds.
- 5. <u>NTP-A169 Set Up CTC Network Access</u>-Continue with this procedure to provision the IP address, default router, subnet mask, and network configuration settings.
- 6. <u>NTP-A358 Set up the ONS 15454 in Secure Mode</u>-Continue with this procedure to connect the CTC in secure mode.
- 7. <u>NTP-A360 Enable EMS Secure Access</u>-Continue with this procedure to enable EMS secure access and provide enhanced SFTP and SSH security.
- 8. <u>NTP-A27 Set Up the ONS 15454 for Firewall Access</u>-Continue with this procedure if the ONS 15454 will be accessed behind firewalls.
- 9. <u>NTP-A355 Create FTP Host</u>-Continue with this procedure if to create FTP host for ENE database backup.

- 10. <u>NTP-A28 Set Up Timing</u>-Continue with this procedure to set up the node's SONET timing references.
- 11. <u>NTP-A324 Create Protection Groups</u>-Complete this procedure, as needed, to set up 1:1, 1:N, 1+1, or Y-cable protection groups for ONS 15454 electrical and optical cards.
- 12. <u>NTP-A256 Set Up SNMP</u>-Complete this procedure if Simple Network Management Protocol (SNMP) will be used for network monitoring.
- 13. <u>NTP-A318 Provision OSI</u>-Complete this procedure if the ONS 15454 will be connected in networks with network elements (NEs) that are based on the Open System Interconnection (OSI) protocol stack. This procedure provisions the TID Address Resolution Protocol (TARP), OSI routers, manual area addresses, subnetwork points of attachment, and IP over OSI tunnels.

Purpose	This procedure verifies that an ONS 15454 node provisioned for SONET is ready for turn-up.	
Tools/Equipment	An engineering work order, site plan, or other document specifying the ONS 15454 card installation.	
Prerequisite Procedures Install the Shelf and Backplane Cable Install Cards and Fiber-Optic Cable		
Required/As Needed	Required	
Onsite/Remote	Onsite	
Security Level	Retrieve or higher	

# **NTP-A323 Verify Card Installation**

- 1. Verify that two TCC2/TCC2P cards are installed in Slots 7 and 11.
- 2. Verify that the green ACT (active) LED is illuminated on one TCC2/TCC2P card and the amber STBY (standby) LED is illuminated on the second TCC2/TCC2P card.
  - **Note:** If the TCC2/TCC2P cards are not installed, or if their LEDs are not operating as described, do not proceed. Repeat the <u>"DLP-A36 Install the TCC2/TCC2P Cards"</u> task, or refer to the *Cisco ONS 15454 Troubleshooting Guide* to resolve installation problems before proceeding to Step 3.
- 3. Verify that cross-connect cards (XCVT, XC10G, or XC-VXC-10G) are installed in Slots 8 and 10. The cross-connect cards must be the same type.
- 4. Verify that the green ACT (active) LED is illuminated on one cross-connect card and the amber STBY (standby) LED is illuminated on the second cross-connect card.
  - **Note:** If the cross-connect cards are not installed, or if their LEDs are not operating as described, do not proceed. Repeat the <u>"DLP-A37 Install the XCVT, XC10G, or XC-VXC-10G Cards"</u> task, or refer to the *Cisco ONS 15454 Troubleshooting Guide* to resolve installation problems before proceeding to Step 5.
- 5. If your site plan requires an AIC-I card, verify that it is installed in Slot 9 and its ACT (active) LED displays a solid green light.
- 6. Verify that the DS-1, DS-3, EC-1, and DS3XM cards are installed in Slots 1 to 6 or 12 to 17 as designated by your installation plan.

**Note:** The DS1/E1-56 and DS3/EC1-48 cards can only be installed in Slots 1 through 3 or 15 through 17.

- 7. If Ethernet cards are installed, verify that the correct cross-connect cards are installed in Slots 8 and 10:
  - E100T-12-G and E1000-2-G cards require XC10G or XC-VXC-10G cards.
  - ♦ G1K-4, ML1000-2, ML100X-8, ML100T-12, and CE-1000-4 cards require XC10G or XC-VXC-10G cards if they are installed in Slots 1 to 6 or 12 to 17. If they are installed in Slots 5, 6, 11 and 12, any cross-connect card can be installed.

- ♦ ML-MR-10 cards require XC10G or XC-VXC-10G cards. The ML-MR-10 card is not compatible with the XCVT or XC card.
- CE-MR-10 cards can be installed in Slots 1 to 6 or 12 to 17, and can interoperate with any cross-connect card.
- 8. If an E1000-2, E1000-2-G, G1K-4, ML100X-8, ML1000-2, CE-1000-4, CE-MR-10, or ML-MR-10 Ethernet card is installed, verify that it has a Gigabit Interface Converter (GBIC) or Small Form-Factor Pluggable (SFP) installed. If not, see the <u>"DLP-A469 Install a GBIC or SFP/XFP</u> <u>Device"</u> task.
- 9. Verify that the OC-N cards (OC-3, OC-3-8, OC-12, OC-12-4, OC-48, OC-48 any slot [AS], OC-192, MRC-2.5G-4, and MRC-12) are installed in the slots designated by your site plan.
  - ◆ OC-3, OC-12, OC-48 AS, MRC-2.5G-4, and MRC-12 cards can be installed in Slots 1 to 6 or 12 to 17.
  - OC-3-8 and OC-12-4 cards can be installed in Slots 1 to 4 and 14 to 17.
  - OC-192 cards can be installed in Slots 5, 6, 12, or 13.
- 10. Verify that the correct cross-connect cards are installed in Slots 8 and 10:
  - ♦ If an OC-192, OC-12-4, or OC-3-8 card is installed, an XC10G card must be installed.
  - ♦ If an OC-48 AS card is installed in Slots 1 to 4 or 14 to 17, an XC10G card must be installed. If XC or XCVT cards are installed, the OC-48 AS can be installed only in Slots 5, 6, 12, or 13.
- 11. Verify that all installed OC-N cards display a solid amber STBY LED.
- 12. If transponder or muxponder cards are installed (TXP\_MR\_10G, TXP\_MR\_2.5G, TXPP\_MR\_2.5G, MXP\_MR\_2.5G, MXPP\_MR\_2.5G, MXP\_2.5G\_10G, TXP\_MR\_10E, TXP\_MR\_10E\_L,
  - TXP\_MR\_10E\_C, MXP\_2.5G\_10E, MXP\_2.5G\_10E\_C, MXP\_2.5G\_10E\_L,

MXP\_MR\_10DME\_L, MXP\_MR\_10DME\_C, ADM-10G, GE\_XP, and 10GE\_XP), verify that they are installed in Slots 1 to 6 or 12 to 17 and have GBIC or SFP connectors installed. For information about installing and provisioning TXP and MXP cards, refer to the Cisco ONS 15454 DWDM Procedure Guide.

- 13. If Fibre Channel cards (FC-MR-4) are installed, verify one of the following:
  - If XC10G cross-connect cards are installed, the FC-MR-4 is installed in Slots 1 to 6 or 12 to 17 and displays a solid green ACT (Active) LED.
  - If XCVT cross-connect cards are installed, the FC-MR-4 is installed in Slots 5 to 6 or 12 to 13 and displays a solid green ACT (Active) LED.
- 14. Verify that fiber-optic cables (fiber) are installed and connected to the locations indicated in the site plan. If the fiber is not installed, complete the <u>NTP-A247 Install Fiber-Optic Cables</u>.
- 15. Verify that fiber is routed correctly in the shelf assembly and fiber boots are installed properly. If the fiber is not routed on the shelf assembly, complete the <u>NTP-A245 Route Fiber-Optic Cables</u>. If the fiber boots are not installed, complete the <u>"DLP-A45 Install the Fiber Boot"</u> task.
- 16. Verify that the software release shown on the LCD matches the software release indicated in your site plan. If the release does not match, perform one of the following procedures:
  - Perform a software upgrade using a Cisco ONS 15454 software CD. Refer to the release-specific software upgrade document for instructions.
  - Replace the TCC2/TCC2P cards with cards containing the correct release. Refer to the *Cisco* ONS 15454 Troubleshooting Guide.
    - Stop. You have completed this procedure.

## NTP-A30 Create Users and Assign Security

Purpose	This procedure creates ONS 15454 users and assigns their security levels.	
Tools/Equipment	None	
Prerequisite Procedures	s NTP-A323 Verify Card Installation	
Required/As Needed	As needed	

Onsite/Remote	Onsite or remote	
Security Level	Superuser	

1. Complete the <u>"DLP-A60 Log into CTC"</u> task at the node where you need to create users. If you are already logged in, continue with Step 2.

**Note:** You must log in as a Superuser to create additional users. The CISCO15 user provided with each ONS 15454 can be used to set up other ONS 15454 users. You can add up to 500 users to one ONS 15454.

2. Complete the <u>"DLP-A74 Create a New User on a Single Node"</u> task or the <u>"DLP-A75 Create a New User on Multiple Nodes"</u> task as needed.

Note: You must add the same user name and password to each node a user will access.

- 3. As needed, complete the <u>"DLP-A456 Configure the Node for RADIUS Authentication"</u> task. Remote Authentication Dial in User Service (RADIUS) validates remote users trying to connect to the network.
- 4. If you want to modify the security policy settings, including password aging and idle user timeout policies, complete the <u>NTP-A205 Modify Users and Change Security</u>.

Stop. You have completed this procedure.

### NTP-A25 Set Up Name, Date, Time, and Contact Information

Purpose	This procedure provisions identification information for the node, including the node name, a contact name and phone number, the location of the node, and the date, time, and time zone.	
Tools/Equipment	None	
Prerequisite Procedures	NTP-A323 Verify Card Installation	
Required/As Needed	As needed	
<b>Onsite/Remote</b>	Onsite or remote	
Security Level	Provisioning or higher	

- 1. Complete the <u>"DLP-A60 Log into CTC"</u> task for the node you will turn up. If you are already logged in, continue with Step 2.
- 2. Click the **Provisioning > General** tabs.
- 3. Enter the following information in the fields listed:
  - ♦ Node Name-Type a name for the node. For Transaction Language 1 (TL1) compliance, names must begin with an alpha character and have no more than 20 alphanumeric (a-z, A-Z, 0-9) characters.
  - Contact-(Optional) Type the name of the node contact person and the phone number, up to 255 characters.
  - ♦ Latitude-Enter the node latitude: N (North) or S (South), degrees, and minutes (optional).
  - Longitude-Enter the node longitude: E (East) or W (West), degrees, and minutes (optional).
     Tip: You can drag and drop the node icon on the network view map to position nodes manually. To create the same network map visible for all ONS 15454 users, complete the NTP-A172 Create a Logical Network Map.

**Note:** The latitude and longitude values only indicate the geographical position of the nodes in the actual network and not the CTC node position.

- Description-Type a description of the node. The description can be a maximum of 255 characters.
- Use NTP/SNTP Server-When checked, CTC uses a Network Time Protocol (NTP) or Simple Network Time Protocol (SNTP) server to set the date and time of the node.

If you do not use an SNTP or NTP server, complete the Date and Time fields. The ONS 15454 will use these fields for alarm dates and times. By default, CTC displays all alarms in the CTC computer time zone for consistency. To change the display to the node time zone, complete the [[ONS 15454 Procedure Guide R8.5.1 -- DLPs A100 to A199#DLP-A112 Display Alarms and Conditions Using Time Zonel"DLP-A112 Display Alarms and Conditions Using Time Zone" task.

**Note:** Using an NTP or SNTP server ensures that all ONS 15454 network nodes use the same date and time reference. The server synchronizes the node's time after power outages or software upgrades.

If you check the Use NTP/SNTP Server check box, type the IP address of one of the following:

- ◊ An NTP/SNTP server connected to the ONS 15454
- ♦ Another ONS 15454 with NTP/SNTP enabled that is connected to the ONS 15454

If you check gateway network element (GNE) for the ONS 15454 SOCKS proxy server (see "DLP-A249 Provision IP Settings" task), external ONS 15454s must reference the gateway ONS 15454 for NTP/SNTP timing. For more information about the ONS 15454 gateway settings, refer to the "Management Network Connectivity" chapter in the *Cisco ONS 15454 Reference Manual*.

**Caution!** If you reference another ONS 15454 for the NTP/SNTP server, make sure the second ONS 15454 references an NTP/SNTP server and not the first ONS 15454 (that is, do not create an NTP/SNTP timing loop by having two ONS 15454 nodes reference each other).

- ♦ Date-If Use NTP/SNTP Server is not checked, type the current date (mm/dd/yyyy, for example, September 24, 2002 is 09/24/2002).
- ◊ Time-If Use NTP/SNTP Server is not checked, type the current time in the format hh:mm:ss, for example, 11:24:58. The ONS 15454 uses a 24-hour clock, so 10:00 PM is entered as 22:00:00.
- ◊ Time Zone-Click the field and choose a city within your time zone from the drop-down list. The list displays the 80 World Time Zones from -11 through 0 (GMT) to +14. Continental United States time zones are GMT-05:00 (Eastern), GMT-06:00 (Central), GMT-07:00 (Mountain), and GMT-08:00 (Pacific).
- ◊ Use Daylight Savings Time-Check this check box if the time zone that you chose uses Daylight Savings Time.
- Insert AIS-V on STS-1 SD-P-Check this check box if you want Alarm Indication Signal Virtual Tributary (AIS-V) conditions inserted on VT circuits carried by STS-1s when the STS-1 crosses its Signal Degrade Path (SD-P) bit error rate (BER) threshold. On protected circuits, traffic will be switched. If the switch cannot be performed, or if circuits are not protected, traffic will be dropped when the STS-1 SD-P BER threshold is reached.
- ♦ SD-P BER-If you selected Insert AIS-V, you can choose the SD-P BER level from the SD-P BER drop-down list.
- 4. Click Apply.
- 5. In the confirmation dialog box, click Yes.
- Review the node information. If you need to make corrections, repeat Steps 3 through 5 to enter the corrections. If the information is correct, continue with the <u>NTP-A261 Set Power Monitor</u> <u>Thresholds</u>.

#### Stop. You have completed this procedure.

## **NTP-A261 Set Power Monitor Thresholds**

Purpose	This procedure provisions extreme high, high, extreme low, and low input battery power thresholds within a -48 volts direct current (VDC) environment. When the thresholds are crossed, the TCC2/TCC2P generates warning alarms in CTC.
Tools/Equipment	None
Prerequisite Procedures	NTP-A323 Verify Card Installation
Required/As Needed	Required
<b>Onsite/Remote</b>	Onsite or remote
Security Level	Provisioning or higher

- 1. Complete the <u>"DLP-A60 Log into CTC"</u> task for the node you will set up. If you are already logged in, continue with Step 2.
- 2. In node view, click the **Provisioning > General > Power Monitor** tabs.
- 3. To change the extreme low battery voltage threshold in 0.5 VDC increments, choose a voltage from the ELWBATVG(Vdc) drop-down list.
- 4. To change the low battery voltage threshold in 0.5 VDC increments, choose a voltage from the LWBATVG(Vdc) drop-down list.
- 5. To change the high battery voltage threshold in 0.5 VDC increments, choose a voltage from the HIBATVG(Vdc) drop-down list.
- 6. To change the extreme high battery voltage threshold in 0.5 VDC increments, choose a voltage from the EHIBATVG(Vdc) drop-down list.
- 7. Click Apply.

### Stop. You have completed this procedure.

### NTP-A169 Set Up CTC Network Access

Purpose	This procedure provisions network access for a node, including its subnet mask default router, Dynamic Host Configuration Protocol (DHCP) server, IIOP (Internet Inter-Orb Protocol) listener port, SOCKS proxy server settings, dual II address setting, static routes, Open Shortest Path First (OSPF) protocol, Routing Information Protocol (RIP), and designated SOCKS servers.	
Tools/Equipment	None	
Prerequisite Procedures	NTP-A323 Verify Card Installation	
Required/As Needed	Required	
Onsite/Remote	Onsite or remote	
Security Level	Superuser	

1. Complete the <u>"DLP-A60 Log into CTC"</u> task. If you are already logged in, continue with Step 2.

2. Complete the <u>"DLP-A249 Provision IP Settings"</u> task to provision the ONS 15454 IP address, subnet mask, default router, DHCP server, IIOP listener port, and SOCKS proxy server settings.

**Tip:** If you cannot log into the node, you can change its IP address, default router, and network mask by using the LCD on the ONS 15454 fan-tray assembly (unless LCD provisioning is suppressed). See the <u>"DLP-A64 Set the IP Address, Default Router, and Network Mask Using the LCD"</u> task for instructions. However, you cannot use the LCD to provision any other network settings.

- 3. If you want to turn on the ONS 15454 secure mode, which allows two IP addresses to be provisioned for the node if TCC2P cards are installed, complete the <u>"DLP-A433 Enable Node Secure Mode"</u> task. Refer to the "Management Network Connectivity" chapter in the Cisco ONS 15454 Reference Manual for information about secure mode.
- 4. If static routes are needed, complete the <u>"DLP-A65 Create a Static Route"</u> task. Refer to the "Management Network Connectivity" chapter in the *Cisco ONS 15454 Reference Manual* for further information about static routes.
- 5. If the ONS 15454 is connected to a LAN or WAN that uses OSPF and you want to share routing information between the LAN/WAN and the ONS network, complete the <u>"DLP-A250 Set Up or Change Open Shortest Path First Protocol"</u> task.
- 6. If the ONS 15454 is connected to a LAN or WAN that uses RIP, complete the <u>"DLP-A251 Set Up or Change Routing Information Protocol"</u> task.
- 7. Complete the <u>"DLP-A558 Provision the Designated SOCKS Servers"</u> task after the network is provisioned if SOCKS proxy is enabled and you are experiencing long login and NE discovery times. This can occur in large networks that have a high ENE-to-GNE ratio and a low number of ENEs with LAN connectivity.

If these conditions do not exist, you are completed with this procedure.

#### Stop. You have completed this procedure.

## NTP-A358 Set up the ONS 15454 in Secure Mode

Purpose	This procedure provisions ONS 15454s and CTC computers for secure access.	
Tools/Equipment	None	
Prerequisite Procedures	NTP-A169 Set Up CTC Network Access	
Required/As Needed	As needed	
Onsite/Remote	Onsite or remote	
Security Level	Superuser	

1. In node view, click the **Provisioning > Security > Access** pane.

- 2. Under the EMS Access area, change the Access State to Secure.
- 3. Click Apply. The CTC disconnects and reconnects through a secure socket connection.
- 4. To create a secure connection, enter <u>https://node-address</u>.

**Note:** After setting up a CTC connection in secure mode, http requests are automatically redirected to https mode.

5. A first time connection is authenticated by the **Website Certification is Not Known** dialog box. Accept the certificate and click **OK**. The **Security Error: Domain Name Mismatch** dialog box appears. Click **OK** to continue.

### Stop. You have completed this procedure.

### NTP-A360 Enable EMS Secure Access

Purpose	This procedure enables EMS secure access. This procedure enables enhanced SFTP and SSH security .	
Tools/Equipment	None	
	NTP-A169 Set Up CTC Network Access	

Prerequisite Procedures	
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Superuser

1. In shelf view, click the **Provisioning > Security > Access** pane.

- 2. Under the EMS Access area, change the Access State to Secure.
- 3. Click Apply. The CTC disconnects and reconnects through a secure socket connection.
- 4. Set the listener port value by choosing "Other constant" radio button.

### Stop. You have completed this procedure.

## NTP-A27 Set Up the ONS 15454 for Firewall Access

Purpose	This procedure provisions ONS 15454s and CTC computers for access through firewalls.	
Tools/Equipment	IIOP listener port number provided by your LAN or firewall administrator	
Prerequisite Procedures	NTP-A323 Verify Card Installation	
Required/As Needed	As needed	
Onsite/Remote	Onsite or remote	
Security Level	Provisioning or higher	

1. Log into a node that is behind the firewall. See the <u>"DLP-A60 Log into CTC"</u> task for instructions. If you are already logged in, continue with Step 2.

2. Complete the <u>"DLP-A67 Provision the IIOP Listener Port on the ONS 15454"</u> task.

<u>Figure 4-1</u> shows an ONS 15454 in a protected network and the CTC computer in an external network. For the computer to access the ONS 15454s, you must provision the IIOP listener port specified by your firewall administrator on the ONS 15454.





3. If the CTC computer resides behind a firewall, complete the <u>"DLP-A68 Provision the IIOP Listener</u> <u>Port on the CTC Computer"</u> task

<u>Figure 4-2</u> shows a CTC computer and ONS 15454 behind firewalls. For the computer to access the ONS 15454, you must provision the IIOP port on the CTC computer and on the ONS 15454.





#### Stop. You have completed this procedure.

### **NTP-A355 Create FTP Host**

Purpose	This procedure provisions FTP Host for access to ENEs for database backup. Use this procedure for database backup with FTP if proxy/firewall is enabled.	
Tools/Equipment	None	
Prerequisite Procedures	NTP-A169 Set Up CTC Network Access NTP-A27 Set Up the ONS 15454 for Firewall Access	
Required/As Needed	As needed	
<b>Onsite/Remote</b>	Onsite or remote	
Security Level	Superuser	

- 1. Complete the <u>"DLP-A60 Log into CTC"</u> task. If you are already logged in, continue with Step 2.
- 2. If you want to turn on the ONS 15454 secure mode, which allows two IP addresses to be provisioned for the node if TCC2P cards are installed, complete the <u>"DLP-A433 Enable Node Secure Mode"</u> task. Refer to the "Management Network Connectivity" chapter in the Cisco ONS 15454 Reference Manual for information about secure mode.
- 3. In Node view, click the **Provisioning > Network > FTP Hosts** tabs.
- 4. Click Create.
- 5. Enter a valid IP address in the FTP Host Address field. A maximum of 12 host can be entered.
- 6. The Mask is automatically set according to the Net/Subnet Mask length specified in DLP-A249. To change the Mask, click the Up/Down arrows on the **Length** menu.
- 7. Check the **FTP Relay Enable** radio button to allow FTP commands at the GNE relay. If you will enable the relay at a later time, skip to Step 9.
- 8. Enter the time, in minutes, that FTP Relay will be enabled. A valid entry is a number between 0 and 60. The number 0 disallows FTP command relay. After the specified time has elapsed the **FTP Relay Enable** flag is unset and FTP command relay is disallowed.

- 10. Repeat Step 4 through Step 9 to provision additional FTP Host.
  - Stop. You have completed this procedure.

<sup>9.</sup> Click OK.

Purpose	This procedure provisions the ONS 15454 timing.
Tools/Equipment	None
Prerequisite Procedures	NTP-A323 Verify Card Installation
Required/As Needed	Required
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

# NTP-A28 Set Up Timing

- 1. Complete the <u>"DLP-A60 Log into CTC"</u> task at the node where you will set up timing. If you are already logged in, continue with Step 2.
- 2. Complete the <u>"DLP-A69 Set Up SONET External or Line Timing"</u> task if an external building integrated timing supply (BITS) source is available. This is the most common SONET timing setup procedure.
- 3. If you cannot complete Step 2 (an external BITS source is not available), complete the <u>"DLP-A70 Set Up Internal Timing"</u> task. This task can only provide Stratum 3 timing.
- 4. Complete the <u>"DLP-A555 Set Up SDH External or Line Timing"</u> task if an external BITS source providing SDH timing (64 KHz, E1, or 2 MHz) is available. Use this task for a SONET shelf running on external SDH timing.

**Note:** For information about SONET timing, refer to the "Timing" chapter in the *Cisco ONS* 15454 *Reference Manual* or to Telcordia GR-253-CORE.

#### Stop. You have completed this procedure.

### **NTP-A324** Create Protection Groups

Purpose This procedure creates ONS 15454 card protection gro		
Tools/Equipment	None	
Prerequisite Procedures NTP-A323 Verify Card Installation		
Required/As Needed As needed		
Onsite/Remote	Onsite or remote	
Security Level	Provisioning or higher	

1. Complete the <u>"DLP-A60 Log into CTC"</u> task at the node where you want to create the protection group. If you are already logged in, continue with Step 2.

<u>Table 4-1</u> describes the protection types available on the ONS 15454.

#### **Table 4-1: Card Protection Types**

Туре	Cards	Description and Installation Requirements
1:1	DS1-14	Pairs one working card with one protect card. The protect card should
		be installed in an odd-numbered slot and the working card in an
	DS3-12	even-numbered slot next to the protect slot towards the TCC2/TCC2P,
		for example: protect in Slot 1, working in Slot 2; protect in Slot 3,
	DS3-12E	working in Slot 4; protect in Slot 15, working in Slot 14. 1:1
		protection can be revertive or nonrevertive. For more information,
	DS3i-N-12	refer to the "Card Protection" chapter and the card reference material
		specific to the card in the Cisco ONS 15454 Reference Manual.
	EC1-12	

	DS3XM-6					
	DS3XM-12					
	DS3/EC1-48					
	DS1N-14	Assigns and matterst and for second unabing ands. The manimum is				
	DS3N-12	1:5. These protect cards must be installed in Slot 3 or 15 and the cards they protect must be on the same side of the shelf.				
	DS3N-12E	Protect cards must match the cards they protect. For example, a				
1:N	DS3i-N-12	DS1N-14 can only protect DS1-14 or DS1N-14 cards. If a failure lears, traffic reverts to the working card after the reversion time has				
	DS3XM-12	elapsed.				
	DS3/EC1-48	For more information, refer to the "Card Protection" chapter and the card reference material specific to the card in the Cisco <i>ONS</i> 15454				
	DS1/E1-56	Reference Manual.				
1+1	Any OC-N	Pairs a working OC-N card/port with a protect OC-N card/port. For multiport OC-N cards, the protect port must match the working port on the working card. For example, Port 1 of an OC-3 card can only be protected by Port 1 of another OC-3 card. The ports on multiport cards must be either working or protect. You cannot mix working and protect ports on the same card. Cards do not need to be in adjoining slots. 1+1 protection can be revertive or nonrevertive, bidirectional or unidirectional.				
Optimized 1+1	OC-3-4 OC-3-8 MRC-2 5G-4 (in OC-3	Ports must be provisioned to SDH. Optimized 1+1 protection is mainly used in networks that have linear 1+1 bidirectional protection schemes. Optimized 1+1 protection is a line-level protection scheme that includes two lines, working and protect. One of the two lines assumes the role of the primary channel, from which traffic gets selected, and the other port assumes the role of the secondary channel, which protects the primary channel. Traffic switches from the primary				
	configurations)	to the secondary channel based on either an external switching command or line conditions. After the line condition or the external switching command that was responsible for a switch clears, the roles of the two sides are reversed.				
Y Cable	MXP_2.5_10G	Pairs a working transponder or muxponder card/port with a protect				
	MXP_2.5_10E	transponder or muxponder card/port. The protect port must be on a different card than the working port and it must be the same card type as the working port. The working and protect port numbers must be				
	MXP_2.5G_10E_C	the same, that is, Port 1 can only protect Port 1, Port 2 can only protect Port 2, etc. For more information, see the <i>Cisco ONS</i> 15454				
	MXP_2.5G_10E_L	DWDM Procedure Guide.				
	MXP_MR_10DME_L					
	MXP_MR_10DME_C					
	TXP_MR_10G					
	TXP_MR_10E					

	TXP_MR_10E_L	
	TXP_MR_10E_C	
	MXP_2.5G_10E	
	MXP_MR_2.5G	
	GE_XP	
	10GE_XP	
Splitter	TXPP_MR_2.5G MXPP_MR_2.5G	Splitter protection is automatically provided with the TXPP_MR_2.5G and MXPP_MR_2.5G cards. For more information, refer to the <i>Cisco ONS 15454 DWDM Procedure Guide</i> .
Unprotected	Any Unprotected cards can cause signal loss if a card fails or incurs protected Any protection, unprotected schemes maximize the service available use on the ONS 15454. Unprotected is the default protection ty	

2. Complete one or more of the following tasks depending on the protection groups you want to create:

- <u>"DLP-A71 Create a 1:1 Protection Group"</u> task
- <u>"DLP-A72 Create a 1:N Protection Group"</u> task
- <u>"DLP-A73 Create a 1+1 Protection Group"</u> task
- DLP-A560 Create an Optimized 1+1 Protection Group

**Note:** If a protect card is not installed, you can complete the <u>"DLP-A332 Change Tunnel Type"</u> task and continue with the card protection provisioning.

**Note:** A 1+1 protection group can only be provisioned between the same equipment type, using the same port number, and the same port rate. The MRC-12 cards used must be in the same slot type; either the low speed-slots or high-speed slots.

**Note:** To create Y-cable protection groups for TXP and MXP cards, refer to the Cisco ONS 15454 DWDM Procedure Guide.

Stop. You have completed this procedure.

Purpose	This procedure provisions the SNMP parameters so that you can use SNMP management software with the ONS 15454.			
Tools/Equipment	None			
Prerequisite Procedures	NTP-A323 Verify Card Installation			
Required/As Needed	eded Required if SNMP is used at your installation.			
Onsite/Remote Onsite or remote				
Security Level Provisioning or higher				

### NTP-A256 Set Up SNMP

1. Complete the <u>"DLP-A60 Log into CTC"</u> task at the node where you want to set up SNMP. If you are already logged in, continue with Step 2.

- 2. In node view, click the **Provisioning > SNMP** tabs.
- 3. In the Trap Destinations area, click **Create**.
- 4. Complete the following in the Create SNMP Trap Destination dialog box (<u>Figure 4-3</u>):

- Destination IP Address-Type the IP address of your network management system. If the node you are logged into is an end network element (ENE), set the destination address to the GNE.
- Community-Type the SNMP community name. For a description of SNMP community names, refer to the "SNMP" chapter in the *Cisco ONS 15454 Reference Manual*.

**Note:** The community name is a form of authentication and access control. The community name assigned to the ONS 15454 is case-sensitive and must match the community name of the network management system (NMS).

• UDP Port-The default User Datagram Protocol (UDP) port for SNMP is 162. (More information about provisioning the UDP port is also given in the <u>"DLP-A449 Set Up SNMP for a GNE"</u> task and the <u>"DLP-A450 Set Up SNMP for an ENE"</u> task.)

**Note:** If the node has the SOCKS proxy server enabled and is provisioned as an ENE, the UDP port must be set to the GNE's SNMP relay port, which is 391.

• Trap Version-Choose either SNMPv1 or SNMPv2. Refer to your NMS documentation to determine whether to use SNMPv1 or SNMPv2.

Figure 4-3: Creating an SNMP Trap

	100
Destination 192.168.10.10 Sample_1	
UDP Port 182 SNMPv1	*

- 5. Click **OK**. The node IP address of the node where you provisioned the new trap destination appears in the Trap Destinations area.
- 6. Click the node IP address in the Trap Destinations area. Verify the SNMP information that appears in the Selected Destination list.
- 7. If you want to set up SNMP remote monitoring (RMON) on gateway node elements (GNEs) and end node elements (ENEs), complete the following tasks as required, depending on the protection groups you want to create:.
  - DLP-A449 Set Up SNMP for a GNE
  - DLP-A450 Set Up SNMP for an ENE
  - DLP-A451 Format and Enter NMS Community String for SNMP Command or Operation

8. Click Apply.

Stop. You have completed this procedure.

### **NTP-A318 Provision OSI**

Purpose	This procedure provisions the ONS 15454 so it can be networked with other vendor NEs that use the OSI protocol stack for data communications network (DCN) communications. This procedure provisions the TID TARP, OSI routers, manual area addresses, subnetwork points of attachment, and IP over OSI tunnels.
Tools/Equipment	None

ONS	15454	Procedure	Guide	R8.5.1	 Turn	Up a	Node
_					 		

Prerequisite Procedures	NTP-A323 Verify Card Installation
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

**Caution!** This procedure requires an understanding of OSI protocols, parameters, and functions. Before you begin, review the OSI reference sections in the "Management Network Connectivity" chapter in the *Cisco* ONS 15454 Reference Manual.

**Caution!** Do not begin this procedure until you know the role of the ONS 15454 within the OSI and IP network.

**Note:** This procedure requires provisioning of non-ONS equipment including routers and third party network elements. Do not begin until you have the capability to complete that provisioning.

- 1. Complete the <u>"DLP-A60 Log into CTC"</u> task at the node where you want to provision the OSI routing mode. If you are already logged in, continue with Step 2.
- 2. As needed, complete the following tasks:
  - DLP-A534 Provision OSI Routing Mode-Complete this task first.
  - <u>DLP-A535 Provision or Modify TARP Operating Parameters</u>-Complete this task next.
  - <u>DLP-A536 Add a Static TID to NSAP Entry to the TARP Data Cache</u>-Complete this task as needed.
  - <u>DLP-A538 Add a TARP Manual Adjacency Table Entry</u>-Complete this task as needed.
  - <u>DLP-A539 Provision OSI Routers</u>-Complete this task as needed.
  - <u>DLP-A540 Provision Additional Manual Area Addresses</u>-Complete this task as needed.
  - <u>DLP-A541 Enable the OSI Subnet on the LAN Interface</u>-Complete this task as needed.
  - <u>DLP-A542 Create an IP-Over-CLNS Tunnel</u>-Complete this task as needed.

Stop. You have completed this procedure.