

## System Log Message Differences

The following system log messages are deprecated in ASA but not in FWSM:

1. %FWSM-6-303003: FTP cmd\_name command denied - failed strict

inspection, terminating connection from  
source\_interface:source\_address/source\_port to  
dest\_interface:dest\_address/dest\_port

2. %FWSM-4-313003: Invalid destination for ICMP error

The following system log messages are present in FWSM but not in ASA:

1. %FWSM-6-106028: Deny TCP (Connection marked for deletion)

from src ip-address/src-port to dst ip-address/dst-port  
flags flag on interface intf-name

2. %FWSM-4-109036: Teardown protocol connection session\_id for

src\_if:src\_ip/src\_port to dest\_if:dest\_ip/dest\_port  
duration duration bytes bytes due to Uauth timeout

3. %FWSM-4-109037: Authentication cannot be done for the user

from src\_ip to dest\_ip for application since auth\_proto  
client is too busy

4. %FWSM-4-109039: Func\_ID: Uauth Unproxy Failed due to the

reason: Failed\_Reason

5. %FWSM-3-202012: Connection rate limit exceeded conns/rate-limit

(per seconds) for dir packet from source\_address/source\_port to  
dest\_address/dest\_port on interface interface\_name

6. %FWSM-6-302022: Built IP protocol 103 connection 219025360

for int\_112:172.16.2.1 (172.16.2.1) to int\_102:172.16.112.2  
(172.16.112.2)

7. %FWSM-6-302023: Teardown IP protocol 103 connection

219025359 for int\_102:172.16.2.1 to int\_112:172.16.112.2

## System\_Log\_Message\_Differences

duration 0:00:35 bytes 74

8. FWSM-6-622002:%d: Teardown BGP Peering session with %A

and AS #%%d\n, BGP\_PEER\_SES\_TEAR\_DOWN

9. %FWSM-2-709008: Configuration may be out of sync between

Active/Standby units

The following table shows system log messages that are present in both FWSM and ASA software, but the text in FWSM software is different from that in ASA software.

FWSM	ASA
%FWSM-6-302024: Pre-allocated H323 GUP connection for faddr intf: {foreign-address/foreign-port} to laddr intf: {local-address/local-port}	%ASA-6-302033:Pre-allocated H323 GUP Connection for faddr interface:foreign address/foreign-port to laddr interface:local-address/local-port
%FWSM-4-302025: Unable to Pre-allocate H323 GUP Connection for faddr  intf: {foreign-address/foreign-port} to laddr intf: {local-address/local-port}	%ASA-4-302034: Unable to pre-allocate H323 GUP Connection for faddr  interface: foreign address/foreign-port to laddr interface:local-address/local-port
%FWSM-4-109035: Authentication failed for user username as the password expired	%ASA-3-109035: Exceeded maximum number (999) of DAP attribute instances for user string.
%FWSM-6-609001: Built local-hostinterface_name:IP_address	%ASA-7-609001: Built local-hostinterface_name:IP_address
%FWSM-6-609002: Teardown local-host interface_name:IP_address duration time	%ASA-7-609002: Teardown local-host interface_name:IP_address duration time
FWSM-6-622001:%d: Built BGP Peering session with %A and AS #%%d\n, BGP_PEER_SES_ESTABLISH	%ASA-6-622001: string tracked route network mask address, distance number, table string, on interface interface-name