

Go to: [Compatibility Matrix for Unified CCE](#)

Go to: [Category:Unified Contact Center Enterprise](#)

Introduction

This compatibility matrix specifies all supported configurations and versions for Cisco Unified Contact Center Enterprise 8.0(x).

Details are also provided about Unified ICM ACD Software Compatibility.

The information in this compatibility matrix supersedes compatibility information in any other Cisco Unified Contact Center Enterprise documentation. If a configuration or version is not stated, that configuration or version is not supported.

Contents

- [1 Unified CCE 8.0\(x\) Product Sets](#)
- [2 Unified CCE 8.0\(x\) Notes](#)
- [3 General Compatibility Notes and Limitations](#)
- [4 Unified CCE Parent / Child PG Compatibility](#)
- [5 NAM/CICM Compatibility](#)
- [6 VDI & Cisco VXI Support](#)
- [7 Application Virtualization](#)
- [8 Siebel Compatibility](#)
- [9 ICM-to-ICM Gateway Requirements](#)
 - ◆ [9.1 ICM-to-ICM Gateway Client and Server Release Requirements](#)
- [10 IP Phone Support](#)
- [11 Other Product Sets](#)
 - ◆ [11.1 Unified ICM ACD 8.0 Product Sets](#)
 - ◇ [11.1.1 Alcatel](#)
 - ◇ [11.1.2 Aspect Call Center w/CMI](#)
 - ◇ [11.1.3 Aspect Spectrum with Lan Transaction Link](#)
 - ◇ [11.1.4 Avaya](#)
 - [11.1.4.1 Avaya CMS RTA Support Matrix](#)
 - [11.1.4.2 AES/CVLAN Server and CVLAN Client Support Matrix](#)
 - [11.1.4.3 Avaya Aura Communications Manager Support Matrix](#)
 - [11.1.4.4 Avaya ARS Support Matrix](#)
 - ◇ [11.1.5 Avaya/Nortel](#)
 - [11.1.5.1 Avaya Aura Contact Center \(AACC\), Nortel Contact Center Manager \(NCCM, formerly Symposium \(SCCS\)\)](#)
 - ◇ [11.1.6 Nortel SDK](#)
 - ◇ [11.1.7 DMS 1000](#)
 - ◇ [11.1.8 SL 100](#)
 - ◆ [11.2 CTI Support for ACD Types](#)

Unified CCE 8.0(x) Product Sets

| Unified CM | IVR (IP-IVR and | PG/CAD/CTI OS Server | CTI OS Desktop | Unified Intelligence | Unified EIM/WIM | Unified CRM Version | RSM | Unified CCMP |
|------------|-----------------|----------------------|----------------|----------------------|-----------------|---------------------|-----|--------------|
|------------|-----------------|----------------------|----------------|----------------------|-----------------|---------------------|-----|--------------|

Unified_CCE_Software_Compatibility_Matrix_for_8.0(x)

| | CVP [formerly ISN]) | | | Center | | | | |
|----------------------------|---|--|--|--------------------------------------|--|--|-------------------------|------------------|
| 8.0(3) 8.0(2) 8.0(1) | IP IVR 8.0(x) CVP 8.5(x) 8.0(1) | PG 8.0(x) 7.5(X) 7.2(X) 7.1(X) CAD 7.5 CTI OS 8.0(x) 7.5(X) 7.2(X) 7.1(X) | 8.0(x) 7.5(x) 7.2(x) 7.1(x) 7.0(x) | 9.1(x) 9.0(x) 8.5(x) 8.0(x) | 9.0(2) 9.0(1) 4.4(1) 4.3(2) 4.3(1) | CRM for Siebel 8.0(x) CRM for PeopleSoft 1.1 (2) CRM for Salesforce 1.1 (2) CRM for Microsoft Dynamics CRM 1.1 (2) CRM for SAP 1.0(2) | 9.1(1) 9.0(1) 8.0 | 8.5(x) 8.0(x) |
| 7.1(5) 7.1(3) 7.1(2) | IP IVR 8.0(x) 7.0(x) CVP 8.5(x) 8.0(1) 7.0(2) | PG 8.0(x) 7.5(x) 7.2(x) 7.1(x) CAD 7.5 CTI OS 8.0(x) 7.5(x) 7.2(x) 7.1(x) | 8.0(x) 7.5(x) 7.2(x) 7.1(x) 7.0(x) | 9.1(x) 9.0(x) 8.5(x) 8.0(x) | 9.0(2) 9.0(1) 4.4(1) 4.3(2) 4.3(1) | CRM for Siebel 8.0(x) CRM for PeopleSoft 1.1 (2) CRM for Salesforce 1.1 (2) CRM for Microsoft Dynamics CRM 1.1 (2) CRM for SAP 1.0(2) | 9.1(1) 9.0(1) 8.0 | 8.5(x) 8.0(x) |

Unified CCE 8.0(x) Notes

1. Unified CCE 8.0(2) or later is required for deployments that are integrated with Genesys Cisco T-Server.
2. Unified CCE 8.0 (1) Central Controller supports PGs running at the following versions for backward compatibility: 7.1(x), 7.2(x), 7.5(x).
3. Multiline Agent Feature is supported only with Unified CM 7.1(3) and later.
4. Outbound Option SIP Dialer:
Supports ISR G2 (39xx and 29xx) with PVDM2 or PVDM3 DSP card
Also supports 28xx, 38xx, AS5350xm, AS5400xm gateways with a PVDM2 DSP card

When needed for design, requires Cisco Unified SIP Proxy Version 1.4.1 or later

Supports IOS Release 15.1(x)T

CUBE cannot be used as a SIP proxy for the SIP dialer. However, CUBE is allowed between the Gateways and rest of UCCE/ICM solution only when implementing MediaSense. Please reference the MediaSense SRND for full implementation details.

5. Unified CM:

Unified CM 8.0 (1) is only supported with an Unified CCE 8.0(1) Peripheral Gateway (PG)

Unified CM features Join/Transfer Across Lines are supported only with Unified CM 7.1(3) and later

6. CTI OS:

The Client version must be at the same version of CTI OS Server or earlier

The CTI OS Server and the PG must be in the same maintenance release version.

7. Unified CVP: For required IOS versions for Gateways and Gatekeepers, see the Hardware and System Software Specification for Cisco Unified Customer Voice Portal.

8. Unified Expert Advisor requires:

Unified CCE 7.2(3) or Unified CCE 7.5(5) or Unified CCE 8.0(1)

Cisco Unified Personal Communicator 7.0 or Microsoft Office Communicator Server (and client) 2007 R2

Cisco Unified Presence Server 7.0(4) or Cisco Unified Presence Server 8.0(2)

CVP is optional, but only 7.0(2) is supported with Expert Advisor 7.6(1)

9. Enhancements were made to CMB 7.1(3) to support RT/RT-lite phones and other CUCM 8.0 features. These changes cannot be back ported to CMB versions 7.1(1) and 7.1(2). These versions will continue to work with ALL versions of UCCE, but WITHOUT support for multiline for Roundtable and Roundtable-Lite endpoints, and enhanced Administration UI. All versions of CMB support Callback/Blended Collaboration features.

10. CMB 7.1(3) minor release is compatible with UCCE 8.0(x) and above, and NOT backward compatible with older versions.

11. Backward compatible PGs are intended to be supported during the transition when you upgrade the Central Controller and PGs to the same version.

12. MR PG and Dialer must be at the same version.

General Compatibility Notes and Limitations

| Component | Notes |
|-----------|---|
| Phones | <p>The following general limitations pertain to IP phones used with Unified CCE Enterprise deployments:</p> <ul style="list-style-type: none"> • Third-party SIP phones are not supported as contact center agent phones. The SIP standard does not include the necessary messaging for third-party Call Control (3PCC). Unified CCE relies on CTI capabilities on the SIP phones that third-party phones do not have. As an alternative, you may choose to deploy the Mobile Agent solution to enable Cisco Unified CCE and Contact Center Hosted (CCH) to use any phone as an agent phone. Please consult with your Cisco Sales Engineer for additional detail on this configuration. • IP Communicator is not supported with Cisco Agent Desktop (CAD) IP Phone Agent. • See the Cisco Unified Communications Manager Compatibility Guide for SIP and other phone protocol support. |
| | |

| | |
|--|---|
| System Peripheral Gateway (PG) Deployments | <p>The following general limitations pertain to Unified CCE deployments that use the System PG:</p> <ul style="list-style-type: none"> E-Mail Manager Option, Web Collaboration Option (both end-of-life products), as well as E-Mail Interaction Manager and Web Interaction Manager (Unified EIM/WIM) are not supported with deployments that use the System PG. For Unified EIM/WIM documentation, see: Cisco Unified E-Mail Interaction Manager and Cisco Unified Web Interaction Manager. |
|--|---|

Unified CCE Parent / Child PG Compatibility

| Release | Parent PG 7.2(x) | Parent PG 7.5(x) | Parent PG 8.0(x) |
|-----------------|------------------|------------------|------------------|
| Child PG 7.2(x) | Yes | Yes | Yes |
| Child PG 7.5(x) | Yes | Yes | Yes |
| Child PG 8.0(x) | Yes | Yes | Yes |

NAM/CICM Compatibility

| NAM Version | CICM Version |
|-------------|--------------|
| 8.0 | 7.5 |
| 8.0 | 7.2 |

Note: The columns can be switched for forward compatibility. For example, NAM at 7.5 and CICM at 8.0 is a supported configuration.

VDI & Cisco VXI Support

| Cisco Client Type | Version | Virtual Desktop Infrastructure | OS Compatibility | Cisco VXI Clients |
|---------------------------|---------|--------------------------------|--|---|
| CTI-OS Clients (All CILs) | 8.0(1) | VMWare View 3.0 | Windows 7 32 bit - Supported Windows 7 WoW64 - Unsupported Windows XP 32 bit - Supported | VXC 2100 - N/A VXC 2200 - N/A VXC 2111 - Supported with Cisco Unified IP Phone 8961, 9951, and 9971 VXC 2211 - Supported |
| CTI-OS Clients (All CILs) | 8.0(1) | Citrix XenDesktop 5.0 or 6.0 | Windows 7 32 bit - Supported Windows 7 WoW64 - Unsupported Win XP 32 Bit - Supported | VXC 2100 - Supported with Cisco Unified IP Phone 8961, 9951, and 9971 VXC 2200 - Supported VXC 2111 - N/A VXC 2211 - N/A |
| Cisco Agent Desktop (CAD) | All | Not Supported | Not Supported | Not Supported |

Note:

- UCM Silent Monitoring is the only type of Silent Monitoring that is supported with VXI/VDI.
- Desktop solutions are supported on PC-like devices only that utilize a keyboard and mouse (no tablets or mobile devices supported at this time).
- The customer is not required to use Cisco VXI endpoints in a VDI solution. The customer can use any VDI endpoint that supports the specific Citrix or VMWare VDI solution versions supported by Cisco. The customer is responsible for ensuring that bandwidth and any other deployment considerations ensure that the solution can meet the performance and timing requirements of CTI-OS.
- For information about CAD with thin client and virtual desktop environments, see the Integrating CAD with Thin Client and Virtual Desktop Environments document.

Application Virtualization

Windows Server 2008 R2 (SP1)

| Cisco Client Version | Version | Citrix/XenApp | Remote Desktop Services platform |
|---------------------------|---------|---------------|----------------------------------|
| CTI-OS Clients (All CILs) | 8.0(x) | XenApp 5.0 | Windows Server 2008 R2 (SP1) |

Siebel Compatibility

| Cisco Siebel Driver | Siebel Release |
|---------------------|------------------------|
| 8.0(x) | 7.8(x), 8.0(x), 8.1(x) |

ICM-to-ICM Gateway Requirements

The following are system requirements for ICM-to-ICM Gateway.

- Both Client ICM and Server ICM must be supported releases of Unified ICME and the two versions must appear on a single row in the table below. If two connected ICMs are running with different releases of Unified ICME, only the ICM-to-ICM Gateway features supported by the lowest release are available.

ICM-to-ICM Gateway Client and Server Release Requirements

| Client/Server 1 | Client/Server 2 | Comments |
|-----------------|-----------------|---------------------------------|
| 7.5, 8.0 | 8.0, 7.5 | UCCE 8.0(1) is a major release. |

IP Phone Support

| IP Phones | Supported | Notes |
|-----------------|-----------|--|
| 99xx series | Y | 9951 and 9971 are supported. |
| 89xx series | Y | 8961 is supported. |
| 69xx series | Y | 6921, 6941, 6961 are supported. 69xx phones are supported only with a single line configuration with Unified CM 7.1(2,) and are supported with multiple lines with Unified CM 7.1(3) and later. |
| 797x | Y | 7970 model is not supported with Unified CM based Silent Monitor or RSM. |
| 796x | Y | 7960 model is not supported with Unified CM based Silent Monitor or RSM. |
| 794x | Y | 7940 model is not supported with Unified CM based Silent Monitor or RSM. |
| 793x | N | |
| 792x | Y | To use the Cisco Wireless IP Phone 792x as an agent phone and as a Cisco IP Phone Agent, consult and follow the Cisco Wireless IP Phone 792x Design and Deployment Guide to ensure proper operation. It is available at: http://www.cisco.com/go/srnd |
| 791x | Y | 7910, 7911, and 7912 are supported with Unified CCE 8.0 (1). 791x series are not supported by Unified CCE based Silent Monitor or RSM. 7910 and 7912 IP Phones do not support the Desktop Silent Monitor feature. The 7910 SW phone does support this feature. |
| IP Communicator | Y | Versions 7.0 and 8.0 are supported. Version 8.6.0.29 is supported for Release 8.5(x) and later. |

Other Product Sets

Unified ICM ACD 8.0 Product Sets

Alcatel

| ACD Version ¹ | ICM 8.0 |
|--------------------------|---------|
| v2.1 | No |
| v3.2 | No |
| v4.1.1 | No |
| v4.2 | No |
| v5.0 | No |
| v5.1 | No |
| v6.0 | No |
| v6.1 | No |
| v7.1 | No |
| v8.0 | No |

¹ Major ACD versions not listed here should be considered unsupported by Cisco.

Aspect Call Center w/CMI

| Switch Version | CMI (Contact Server) | ICM 8.0 | Notes |
|-------------------|----------------------|---------|--|
| v8.02 | CMI v5.1.1 | No | |
| v8.3 | CMI v5.1.2 | No | |
| v8.3 | CMI v5.2 | No | |
| v8.4 | CMI v5.2 | No | Aspect 8.4 and CMI 5.2 are End of Support (EOS) by Aspect. |
| v9.0 | CMI v5.2 | No | Aspect 9.0 and CMI 5.2 are EOS by Aspect. |
| v9.1 (Win2k3) | CMI v5.2 | Yes | Aspect 9.1 and CMI 5.2 are EOS by Aspect. |
| v9.1.1 | CMI v5.2 | Yes | Aspect 9.1.1 and CMI 5.2 are EOS by Aspect. |
| v9.2 | CMI v5.2 | Yes | |
| v9.2 | CMI v6.2.1 | Yes | |
| v9.3 ¹ | CMI v5.2 | Yes | |
| v9.3 | CMI v6.2.1 | Yes | |
| v9.3 | CMI v6.3 | Yes | |
| v9.3 | CMI v6.4 | No | CMI v6.4 is supported only on Win2k8. |

¹ICM supports four-digit Application IDs and CCT with Aspect Switch Version 9.3 from 7.5(9) onwards in the 7.5(x) stream and 8.0(2) onwards in the 8.(x) stream.

Note: DataInterLink with Application Bridge 6.0 is supported for all versions of ICM.

Aspect Spectrum with Lan Transaction Link

| ACD Version ¹ | ICM 8.0 |
|--------------------------|---------|
| 8.0.0 | No |
| 8.0.0b | No |
| 8.0.0c | No |
| 8.0.0d | No |
| 10.0 | No |
| v10.0 sp1 (R8AM09) | No |
| v10.0 sp2 | No |
| v10.0 sp3 | No |
| 10.0.4 | Yes |
| v10.1 | Yes |

| | |
|-------|-----|
| v10.2 | Yes |
|-------|-----|

¹Major ACD versions not listed here should be considered unsupported by Cisco.

Avaya

When reviewing the support details in the Avaya matrixes below, consider the following notes and special considerations related to Avaya support:

- Avaya Name Changes: Avaya changed names from DEFINITY to MultiVantage to Avaya Communications Manager (ACM) to Avaya Aura Communications Manager.
- RTA 5.0.5 and RTA 6.0 enhanced functionality (60 skills per agent and 2000 skill groups per system) are not supported by ICM.
- ICM currently does not support more than 12000 active associations on a single system.
- All CMS versions are supported as long as a supported RTA is being used.
- Cisco supports the Avaya S8300, S8400, S85XX, S87XX, and S88XX Servers in support of ACM.
- Cisco supports the general use of Avaya IP Phones.
- MAPD is EOL from June 2008.
- Support for third-party ACD clients, SDKs, and interfaces integrated with ICM ends when the third-party ACD manufacturer ends mainstream support.
- Ten-digit Agent extension and Agent ID are supported from ICM 9.0(3) and higher that has ACM 6.2 and higher; AES 6.2 and higher; and CMS R16 with RTA 6.0 pl: 13g.

Avaya CMS RTA Support Matrix

| RTA Version | ICM 8.0 |
|--------------|---------|
| 4.1 | No |
| 4.5 | No |
| 4.6.1 | No |
| 4.6.2 | No |
| 4.6.4 | No |
| 4.6.5 | No |
| 4.7.3 | No |
| 4.8.1 | No |
| 5 | No |
| 5.0.5 | Yes |
| 5.0.5e | No |
| 6.0(x) | Yes |
| 6.0 Extended | No |

AES/CVLAN Server and CVLAN Client Support Matrix

| AES (CVLAN) Server | CVLAN Client Supported | ICM 8.0 | Notes |
|--------------------|--|-----------------|---------------------------------|
| 3.0.x | 8.2.5 | No ⁵ | 8.2.5 client is EOL from Avaya. |
| 3.1.x | 8.2.5 | No ⁵ | 8.2.5 client is EOL from Avaya. |
| 4.0.x | 8.2.5 | No ⁵ | 8.2.5 client is EOL from Avaya. |
| 4.1.x | 4.1.0 ¹ 4.2.2 ² 6.1 ³ | Yes | |
| 4.2.x | 4.1.0 4.2.2 6.1 | Yes | |
| 5.2.1 ⁴ | 4.1.0 4.2.2 6.1 | Yes | |
| 5.2.2 | 4.1.0 4.2.2 6.1 | Yes | |
| 6.1 | 4.1.0 4.2.2 6.1 | Yes | |
| 6.2 | 4.1.0 4.2.2 6.1 | Yes | |
| 6.3 | 4.1.0 4.2.2 6.1 | Yes | |

¹CVLAN Client 4.1.0 is integrated from UCCE/ICM 7.2.7 to 7.5.6.

²CVLAN Client 4.2.2 is integrated from UCCE/ICM 7.5.7 to 8.5.1.

³CVLAN Client 6.1 is integrated from UCCE/ICM 8.5.2 onwards and UCCE/ICM 10.0(x) supports only CVLAN Client 6.1.

⁴Processor Ethernet is supported with AES 5.2.1 and ACM 5.2.1.

⁵Support for third-party ACD clients, SDKs, and interfaces integrated with ICM ends when the third-party ACD manufacturer ends mainstream support.

Avaya Aura Communications Manager Support Matrix

| ACD Version ¹ | ICM 8.0 | Notes |
|--------------------------------|---------|---|
| ACM 2.2.2 | No | |
| ACM 3.0 ² | No | |
| ACM 3.1.0 | No | No support due to Avaya regression fix being provided with 3.1.1. |
| ACM 3.1.1.628.7 Patch 11761 | No | Supported with both AES 3.0 & AES 3.1 in CMS environments. No support in CMS-less with AES. |

Unified_CCE_Software_Compatibility_Matrix_for_8.0(x)

| | | |
|------------------------|-----|--|
| ACM 3.1.2 | No | Supported only in a CMS environment. |
| ACM 3.1.3 | No | Supports both CMS and CMS-Less configurations. |
| ACM 3.1.4 | No | |
| ACM 3.1.5 | No | |
| ACM 4.0 ² | Yes | |
| ACM 4.0.1 | Yes | |
| ACM 4.0.3 | Yes | |
| ACM 4.0.4 | Yes | |
| ACM 5.0 | Yes | |
| ACM 5.1 | Yes | |
| ACM 5.1.2 | Yes | |
| ACM 5.2 | Yes | |
| ACM 5.2.1 ³ | Yes | |
| ACM 6.0 | Yes | |
| ACM 6.2 | Yes | |
| ACM 6.3 | Yes | |

¹Major ACD versions not listed here should be considered unsupported by Cisco.

²Avaya CM 4.x supports both MAPD and AES. However, MAPD is supported only up to ICM 7.2.4.

³Processor Ethernet is supported with AES 5.2.1 and ACM 5.2.1.

Avaya ARS Support Matrix

| ACD Version ¹ | ICM 8.0 |
|--------------------------|---------|
| 4.0 | Yes |
| 4.0.1 | Yes |
| 4.0.3 | Yes |
| 4.0.4 | Yes |
| 5.0 | Yes |
| 5.1 | Yes |
| 5.1.2 | Yes |
| 5.2.1 | No |

¹Major ACD versions not listed here should be considered unsupported by Cisco.

Avaya/Nortel

Caveats and special considerations apply with regard to support of this vendor's ACD/Switch types. Consider the following notes as you review the supported matrixes described below:

- Cisco currently supports only select Succession platforms with Symposium. (See the following chart for details.)

Unified_CCE_Software_Compatibility_Matrix_for_8.0(x)

- SEI Lite integration is available for select ICM versions. The Cisco Automated Administrator for Symposium is required in order to integrate SEI Lite on ICM versions 5.0 and higher. (See the following chart for details.)
- Cisco does not support more than one PG pair connected to a single Symposium server.
- Customers who need to obtain the SCCS Toolkit must request this from Cisco. Please send an email to icm-nortelpg-sdk@cisco.com, and include the following information:
 - ◆ Customer name
 - ◆ Maintenance contract number
 - ◆ ICM version
 - ◆ PG version
 - ◆ Number of PGs

Avaya Aura Contact Center (AACC), Nortel Contact Center Manager (NCCM, formerly Symposium (SCCS))

| AACC/SCCS/NCCM Version | Meridian Succession Version | Nortel SEI Lite | ICM 8.0 | Notes |
|------------------------|---|--|---------|---|
| AACC 6.0 | CS1000 Succession 7.5 CS1000 Succession 7.0 CS1000 Succession 6.0 | Planned | Yes | |
| 5.0 | Meridian Option 11 ² | Yes, SU03 with designer patch (NN_SCCS_5.0_DP_03_S) or SU06 AAS is supported with ICM 6.0(0) SR3, 7.0(0) SR2, and later releases of ICM | No | <ul style="list-style-type: none"> • HDX SDK R5.0 needs to be installed on the PG. • Feature Pack 1 is now supported with SCCS 5.0. • No SWAP feature support prior to 5.0 SR13. |

Unified_CCE_Software_Compatibility_Matrix_for_8.0(x)

| | | | | |
|-----|---|--|-----|--|
| | | | | <ul style="list-style-type: none"> From September 2008, no further support from Nortel will be provided for SCCS 5.0. |
| 5.0 | Succession Communication Server 1000 (CS1K) | Yes, SU03 with designer patch (NN_SCCS_5.0_DP_03_S) or SU06 AAS is supported with ICM 6.0(0) SR3, 7.0(0) SR2, and later releases of ICM | No | From September 2008, no further support from Nortel will be provided for SCCS 5.0. |
| 6.0 | C1000 Succession 4.5 | Yes | Yes | |
| 6.0 | C1000 Succession 5.0 | Yes | Yes | |
| 6.0 | C1000 Succession 5.5 | Yes | Yes | |

¹Starting with UCCE/ICM 8.5(2), the Cisco Nortel PG is supported on both Windows 2008 R2 and Windows 2003 with AACC 6.0 only.

Prior versions of the Cisco Nortel PG are supported only on Windows 2003.

²While Cisco does not have a Nortel Meridian Option 51/61/81C in the testing environment, we do support ICM integration with these

Nortel Meridian models with CCM 5/6 since the PG to Symposium/CCM interface is tested. We have multiple customers running these environments in production. Please note that Nortel has stopped support for CCM 5 and, therefore, our support is limited.

Nortel SDK

| ACD Version ¹ | ICM 8.0 | Notes |
|--|---------|--|
| Nortel SDK 5.0 (with SCCS 5.0 and NCCM 6.0) | No | From September 2008, no further support from Nortel will be provided for SCCS 5.0. |
| Nortel SDK 6.0 (with NCCM 6.0, NCCM 7.0, and AACC 6.0) | Yes | HDX 6, RTD 6 must be installed on the PG. Note: SDKs are not integrated with ICM. |

DMS 1000

| ACD Version ¹ | ICM 8.0 | Notes |
|--------------------------|---------|--|
| NA09 SCAI 11 | No | |
| NA10 SCAI 12 | No | |
| NA10 SCAI 13 | No | |
| Eur08 SCAI 11 | No | |
| Eur09 SCAI 12 | No | |
| Eur10 SCAI 13 | No | |
| APC05 SCAI 10 | No | |
| APC06 SCAI 11 | No | |
| APC07 SCAI 12 | No | |
| APC08 SCAI 13 | No | |
| SCAI 14 | No | |
| SCAI 17 | No | SCAI 17 supported at the server level; client must be at SCAI 11. No new features introduced by Nortel with SCAI 17 are supported. |
| SCAI 18 | No | |

¹Major ACD versions not listed here should be considered unsupported by Cisco.

SL 100

| ACD Version ¹ | ICM 8.0 |
|--------------------------|---------|
| MSLIVD08 SCAI 11 | No |
| MSLIVD09 SCAI 12 | No |
| MSLIVD10 SCAI 13 | No |
| SCAI 17 | No |
| SCAI 18 | No |

¹ Major ACD versions not listed here should be considered unsupported by Cisco.

CTI Support for ACD Types

| ACD Vendor | ACD Model | CTI Server Protocol Support | CTI OS Support |
|------------|---|-----------------------------|----------------|
| Alcatel | 4400 ACD w/CSTA-2 | Yes | Yes |
| Aspect | Contact Server | Yes | Yes |
| Avaya | Avaya Communication Manager driven by Avaya S8300, S8400, S85xx, S87xx, and S88xx | Yes | Yes |

Unified_CCE_Software_Compatibility_Matrix_for_8.0(x)

| | Servers | | |
|----------|-----------------------------------|-----|-----|
| Cisco | IPCC | Yes | Yes |
| Nortel | DMS -100 | Yes | No |
| Nortel | DMS -500 | Yes | No |
| Nortel | SL - 100 | No | No |
| Nortel | Symposium | Yes | Yes |
| Rockwell | Galaxy | No | No |
| Aspect | Spectrum w/ LAN Transaction Link | Yes | Yes |
| Aspect | Spectrum w. X.25 Transaction Link | Yes | Yes |

Back to: [Category:Unified Contact Center Enterprise](#)