

## Voice\_gateway\_debug\_commands\_and\_log\_files

This section provides information about using and interpreting the voice gateway debug commands.

**Note:** The following commands are entered on the gateway's command line through a Telnet session, unless you are directly connected to the gateway.

Description of Command or Issue	Command to Use or Suggestion Regarding Issue
Turn off <b>all</b> debug logging.	no debug all
Clear the gateways' debug logs so that you will have only fresh information related to a call issue.	clear log
Add back specific logging. <ul style="list-style-type: none"> <li>• Default debugging for all dial peers</li> <li>• VXML subsystem entry/exit messages</li> <li>• SIP debugging</li> </ul>	Commands to add back specific logging: <ul style="list-style-type: none"> <li>• debug voip dialpeer default</li> <li>• debug voip app vxml inout</li> <li>• debug ccsip all</li> </ul>
Example Log message received: <b>**CVP**85C28020C56C11DD800ED5D4E76F3954**helloworld**ERROR:</b> 10.86.132.141, CVP VXML Server emergency error occurred such as an invalid application. Call is dropped.	Check the application definition in the gateway configuration. Be sure the name of the application is entered exactly as the application is actually spelled.  For example: <b>HelloWorld</b> , and <b>customhelloworld</b>
You receive a URL in the log file.	Try copying the URL information and pasting it into your browser. The browser

## Voice\_gateway\_debug\_commands\_and\_log\_files

	should display additional information.
--	--

**Back:** [Troubleshooting Tips for Getting Started with CVP](#)